



Dimension			
A	B	C	E
25.00(.984)	30.8(1.213)	16.92(.666)	15.88(.625)
33.32(1.312)	39.2(1.543)	25.25(.994)	
47.04(1.852)	53.1(2.091)	38.96(1.534)	
63.50(2.500)	69.4(2.732)	55.42(2.182)	
25.00(.984)	30.8(1.213)	16.92(.666)	19.05(.750)
33.32(1.312)	39.2(1.543)	25.25(.994)	
47.04(1.852)	53.1(2.091)	38.96(1.534)	
63.50(2.500)	69.4(2.732)	55.42(2.182)	
25.00(.984)	30.8(1.213)	16.92(.666)	22.86(.900)
33.32(1.312)	39.2(1.543)	25.25(.994)	
47.04(1.852)	53.1(2.091)	38.96(1.534)	
63.50(2.500)	69.4(2.732)	55.42(2.182)	

MATERIAL
 Insulator: Glass Filled Polyester UL94V-0
 Contacts: Copper Alloy
 Shell: Steel, Tin plated
 Color: Black

ELECTRICAL
 Operation Voltage: 250 V AC(r.m.s.)
 Current Rating: 3 A
 Contact Resistance: <20mΩ
 Insulation Resistance: >5000 MΩ
 Dielectric Withstanding Voltage: 1000 VAC/minute
 Operating Temperature: -40C ~ +105C

RoHS Compliant

Mounting options.

Part Number

DIMENSION E
 A - 15.88mm
 B - 19.05mm
 C - 22.86mm

A-4-40 Jack screws assembled
 B-Board Locks
 F-Ferrite
 G-Grounding Straps
 J-4-40 Jack Screws (bulk packed)
 R-Riveted 4-40 Jack screws
 T-Threaded Inserts

DP-XXPPXXPPXX-(see options)

PLATING

1= Full Gold Flash/Nickel (STD)
 6= Selective Gold flash/Nickel
 7 = Selective 15u" Gold/Nickel
 8 = Selective 30u" Gold/Nickel
 NON-STD may require MOQ

of circuits
 09, 15, 25, 37

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ON-SHORE TECHNOLOGY, INC. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ON-SHORE TECHNOLOGY, INC.

OST ON-SHORE TECHNOLOGY, INC.							
TITLE		DP Series - Dual Port D-sub, Plug over Plug					
PART NO.	DP-XXPPXX-XXX	DWG NO.	DP-XXPPXX-XXX.DWG				
APPROVED	CHECKED	DESIGNED	DRAWN	4050		Tolerance	
Billy 2001.10.28	Johnn 2001.10.28	Tony 2001.10.28	Steven 2001.10.28	UNIT: mm/inches SCALE: NONE		x ±0.30/.012 .xx ±0.20/.010 .xxx ±0.10/.004	
SHEET: 01/01				REV.: A			