## 0.25 METER LENGTH





Connector A 132117 SMA Jack Straight Brass Gold + Heatshrink 50 Ohm RG-316 Continuity/Hi-Pot Connector B 142233 SMB Jack Right Angle Bulkhead - Rear Mount Brass Gold + Heatshrink

## **Assembly & Label Notes**

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

Connector A			Cable		Connector B	
Part #:	132117	Part #:	RG-316	Part #:	142233	
Description:	SMA JK RG174 RG316 LMR100 50O	Description:	RG-316 - ST 0.102	Description:	SMB R/A BHD JK RG174 RG316 LMR100	
Type:	SMA	Dielectric:	ST	i i	500	
Gender:	Jack	Shielding:	Braid	Type:	SMB	
Body Type:	Straight	Diameter:	0.102	Gender:	Jack	
Contact Type:	Solder	Impedance:	50 Ohm	Body Type:	Right Angle	
Polarity:	Standard	Sheathing:	None	Contact Type:	Solder	
Impedance:	50 Ohm	Testing:	Continuity Hi-Pot	Polarity:	Standard	
Mounting:	Cable	Length:	0.25 Meter	Impedance:	50 Ohm	
Body Material:	Brass			Mounting:	Bulkhead - Rear Mount	
Body Finish:	Gold			Body Material:	Brass	
IP Rating:	None			Body Finish:	Gold	
Contact Material:	Beryllium Copper			IP Rating:	None	
Contact Finish:	Gold			Contact Material:	Brass	
Max. Freg.:	12.4 GHz			Contact Finish:	Gold	
Booting:	SMA Jack Straight			Max. Freq.:	4 GHz	
	· •			Booting:	SMB Jack Right Angle	
				Clocking:	0°	



**CONTROLLED DOCUMENT - DO NOT COPY** 

THIS DRAWING MAY CONTAIN PATENTED OR PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.

SMA-ST-JK/SMB-RA-JK G316 0.25M

Part No:

Q-2V03H0005.25M

UNLESS SPECIFIED TOLER ANCE:

TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: NTER LABEL IF LENC

CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES



## **RoHS 2015/863 Compliance Statement**

According to the manufacture of all the component parts contained in this assembly, this product has been determined to be RoHS Compliant with RoHS Directive 2011/65/EU and as amended by Directive 2015/863, and without material exceptions (RoHS3 Complaint).

For the individual component RoHS certificates used in this assembly, please contact Amphenol Custom Cable.

The RoHS Compliance of any product so designated is based upon evidence from the producer (manufacturers') that the component parts comply with the RoHS Directive. Amphenol Custom Cable has taken all reasonable steps to confirm that the OEM (Manufacturer) of the components used in this assembly have provided evidence regarding the absence of the restricted substances to support the manufacturer's claim of compliance.

To the best of our knowledge and with due diligence, we certify that the product listed herein complies with the RoHS requirements.

**Date:** 10/2/2023

**Part Number:** Q-2V03H0005.25M

Manufacturer: Amphenol Custom Cable

**Description:** SMA-ST-JK/SMB-RA-JK G316 0.25M

This information is valid as of the date indicated for the item (part number) listed.

**Director of Quality Assurance** 

