


ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00901	Connector, dc plug, 3.5x1.35xL16.5mm, molding style, spring contacts	1	
2	30-00404	Wire, 2C TS, 24 AWG, UL2468, 300V, 80C, 3.0 mm, VW-1, PVC, 87A	1	
3	24-00009	Overmold, PVC	1	black



Wiring Diagram	
50-00901	wire color
center	black with stripe
sleeve	black

Notes:
Functionally equivalent components may be substituted

Revision:	Date:	Description:	Prepared:	Notes:	<h1>TENSILITY</h1> <p>tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com</p>
A	02/06/2018	Initial release	GL Digitally signed by GL Date: 2018.03.07 10:06:38 -08'00'	RoHS compliant	
			Verified: JP Digitally signed by JP Date: 2018.03.07 11:11:30 -08'00'	Function test: no open, no short circuit, no intermittent	
			Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Description: Cable, 1830 mm, 3.5x1.35x10 mm 90° 50-00901 dc plug to 10 mm tinned, 24 AWG, UL2468, 30-00404 wire	
				Size: A	Part number: 10-02498
				Scale: 1:1	Sheet 1 of 1

5

4

3

2

1