

1261 (7/68)

APPLICATOR PARTS LIST

TYPE I.D. BAND
ENDFEED

AMP INCORPORATED
HARRISBURG, PENNA. ASSY

QUICK CHANGE ASSY

NO.	DESCRIPTION	REQ.	PART NO.	NO.	DESCRIPTION	REQ.	PART NO.	TERMINALS
1	WIRE CRIMPER	1	319731	42	COMP. SPRING (TABLE)	2	803036-1	40681
2	INS. CRIMPER	1	375687	43	COVER PLATE	2	375680	40942
3	ANVIL	1	375684	44	FEED BLOCK - LEFT	1	376659	41108
4	ANVIL	1	375684	45	FEED BLOCK - RIGHT	1	376658	41276
5	SHEAR BLADE	1	375683	46	FEED LINK	1	376656	
6	REAR SHEAR PLATE	1		47	FEED PIN (FEED BLOCK)	1	376657	
7	SHEAR BLADE SPACER			48				
8	FRONT SHEAR PLATE			49				
9	REAR ANVIL SPACER PLT.			50	TO BE USED ONLY WHEN INDENTING (S REQ'D)			
10	FRONT ANVIL SPACER PLT.			51	INDENTOR HOLDER	1	375676	
11	TOOL SPACER			52	INDENTOR HOLDER KEY	1	376075	
12	CRIMP SPACER			53	INDENTOR HOLDER PIN	1	375675	
13	STRIP GUIDE	1	376662	54	INDENTORS (AS REQ'D)	1	374595	
14	STOCK DRAG	1	376663	55				
15	RAM	1	471667	56	INDENTOR SPACER AS REQ'D	1		
16	TOOL HOLDER	1	471662	57				
17	ADJ. CRIMP MOUNT ASSY	1	379729	58				
18	ADJ. BLOCK	1		59				
19	APPLICATOR MOUNT ASSY.	1		60	INDENTOR SPACER (AS REQ'D)			
20	BASE PLATE	1	471658	61				
21	BASE BLOCK	1	471659	62	SPACER, GUARD	1	693372-1	
22	STRIP GUIDE PLATE FLOATING	1	471660	63				
23	ANVIL HOLDER	1		64	SCREW, DRIVE	3	21017-6	
24	AUX. ANVIL HOLDER	1		65	PLATE, IDENTIFICATION	1	452373-1	
25	STRIPPER	1	375690-1	66	QUICK FEED CHANGE ASSY	1	693308-1	
26	STRIPPER MOUNT	1	377811	67	NUT - HEX JAM 1/4-20	1	1-22202-4	
27	RETAINER PLATE			68				
28	STRIPPER MOUNT BRACKET			69				
29	STRIPPER BUSHING			70				
30	STOCK DRAG CONTROL BRK.	1	465870-1	71				
31	STOCK DRAG HANDLE			72				
32	STOCK DRAG STUD			REV.	REVISION RECORD	DATE	BY	ECN
33	STOCK DRAG SPRING	2	3-22284-9	C3	REIN STATED & REDRAWN	3-14-71	JAM	R2929
34	STOCK DRAG ADJ. SCREW	2	372997	D	REV. PER ECN	7-17-79	JG	R3118
35	FEED FINGER HOLDER	1		E	REV. ITEM 42 PER ECN	1-28-80	JG	R3882
36	FEED FINGER	1	376655-1	F	REV ECN R-6406	5-16-85	JG	R6406
37	FEED FINGER SPRING	1	376661-1					
38	FEED FINGER PIN	1	21030-7					
39	BASE CASTING	1	570238					
40	GUARD	1	469401-1					
41	TABLE MOUNTS	2	3756689					

CRIMPING DATA		TERMINALS
TO APPLY TERMINAL		40681
WIRE SIZE	CRIMP HEIGHT	40942
		41108
		41276
CRIMP SIZE	TYPE	FEED
WIRE	—H—	.312
INSUL.	.220	.624
SLEEVED	—H—	.936
INSULATION RANGE	WIRE RANGE	
125-.220	—H—	
EXPLODED VIEW		
A-6012-1	6012-2	
REMARKS:		
ADJ. INS. CRIMPER		
ONE, TWO, OR THREE		
TERMINALS AT A TIME		
WITH - QUICK FEED		
CHANGE ASS'Y		
△ TO BE USED WHEN		
INDENTOR HOLDER		
IS NOT REQ'D.		
■ DENOTES WEARING PARTS		
RECOMMEND PURCHASE REPLACEMENT		
THIS APPLICATOR IS TO BE USED ON		
AMP-O-ELECTRIC		
MECH. FEED 692140-1		DIST. 4
SERIAL NO.	DATE SHIPPED	DESIGNED
		K. STAKEM
		3-13-79
CUSTOMER NAME AND ADDRESS		3/13/79
		3/16/79
APPLICATOR NUMBER	REV.	APPROV.
F 1-671505-0	1 OF 1	JAM
		3/19/79
		SHEET

FOR HARDWARE SEE 687531-1