

THESE DRAWINGS ARE THE PROPERTY OF QUALTEK ELECTRONICS AND NOT TO BE REPRODUCED FOR OR COMMUNICATED TO A THIRD PARTY WITHOUT THE EXPRESS WRITTEN PERMISSION OF AN OFFICER OF QUALTEK ELECTRONICS.

| REVISION | | | | | | |
|----------|-------------|------|----------|--|--|--|
| REV. | DESCRIPTION | DATE | APPROVED | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |





CONTROLLED

NOTES:

- 1. CORDAGE: H05VV-F, 3x0.75mm, UNSHIELDED, CEE COLOR CODE, TEMP. RATING 70°C, RATING: 250V 6A, JACKET COLOR: BLACK
- 2. PLUG: IEC 884/CEE7-VII
- 3. OTHER END: ROJ 50mm STRIP 5mm
- 4. APPROVALS: GERMANY, SWITZERLAND, DENMARK, NORWAY, FINLAND, FRANCE, BELGIUM, ITALY, NETHERLANDS, SWEDEN, AUSTRIA
- ROHS COMPLIANT

| Dim range | Tolerance +/- | Qualtek Electronics Corp. PPC DIVISION | | |
|--------------|------------------|---|----------------|-------------------|
| (mm) | (mm) | Part Number: | 366040-D01 | RoHS Compliant |
| 0-1 | 0.15 | Description: POWER CORD | | |
| 1-6 | 0.20 | POWER CORD | | |
| 6-18 | 0.30 | | LINUT | |
| 18-50 | 0.50 | | UNIT: mm | |
| 50-120 | 0.70 | Drawn / Date | Checked / Date | Approved / Date |
| 120-250 | 0.90 | R.Nuti | 08-21-07 | JJH / 08-21-07 |
| 250-500 | 1.20 | 08-21-07 | | |