<u>M</u> 1/1	CL575-0107-8-71 ,	CL575	CODE NO.	ELECTRIC CO., LTD.	HIROSE	:
>	X5-56S2A-DSA (71)	F	PART NO.	SPECIFICATION SHEET	SPEC	T S
-21	ELC4-151416-	IG NO.	DRAWING NO	AT:Assurance Test X:Applicable Test	QT:Qualification Test AT:A	Note QT:Qua
06.10.04	AK.SUZUKAWA	DRAWN		specified, refer to JIS C 5402	erwise specified,	Unless otherwise
06.10.04	HS.OZAWA KY.NAKAMURA	CHECKED		© THIS STORAGE INDICATES A LONG-TERM STORAGE STATE FOR THE UNUSED PRODUCT BEFORE THE BOARD MOUNTED.	HIS STORAGE INDICA FOR THE UNUSED PRO	T (2)
06.10.04	HS OKAWA	APPROVED			TEMPERATURE RISE	REMARK (1)
DATE	CHECKED		DESIGNED	DESCRIPTION OF REVISIONS		COUNT
	5 % OF THE SURFACE	OVER A MINIMUM OF 95 BEING IMMERSED.	OVER A I	FOR IMMERSION DURATION, 3 s.	240±5°C	
× × I	G OF SOLDE	NIFORM COA	<u> </u>	2) SOLDERING IRONS : 360°C FOR 5 s MAX SOLDERED AT SOLDER TEMPERATURE		SOLDRABILITY
×	CASE OF EXCESSIVE	NO DEFORMATION OF CASE OF		(TEST STANDARD: JEIDA-39) 1) SOLDER BATH:SOLDER TEMPERATURE, 260 + 5°C EOB IMMERSION DIREATION 10 + 1		RESISTANCE TO
×	OSION.	NO HEAVY CORROSION	NO NO H	ED IN 10 PPM FOR 96 h.		SULPHER DIOXIDE
× ×	CONTACT RESISTANCE: 60 mΩ MAX. NO DAMAGE, CRACK AND LOOSENESS OF PART CONTACT RESISTANCE: 60 mΩ MAX.	CONTACT RESISTANCE: NO DAMAGE, CRACK AN OF PART CONTACT RESISTANCE:		ED AT 85°C, 96 h.	SALT MIST EXPOSED IN	DRY HEAT CORROSION SALT
×	D LOOS	NO DAMAGE, CRA OF PARTS.		RE-55 \rightarrow +15 \sim +35 \rightarrow +85 \rightarrow +15 \sim \rightarrow 2 \sim 3 \rightarrow 30 \rightarrow 2 \sim 3 min CYCLES.	OF	RAPID CHANGE TEMPERATURE
×	CONTACT RESISTANCE: 60 mΩ MAX. INSULATION RESISTANCE: 100 MΩ MIN.	CONTACT RESISTANCE: INSULATION RESISTANC	h. ① CON	EDAT 40 ±2 °C, 90 \sim 95%, 96	TE) EXPOSED AT	(STEADY STATE)
				HARACTERISTICS	\circ	ENVIRONMENTAL
×		OF PARTS.		DURATION IMES FOR 3	490 m/s ² , AT 3 T	SHOCK
×	NO ELECTRICAL DISCONTINUITY OF 1	NO ELECTRICAL Γ 1 μs. NO DAMAGE, CRA	© NOE	FREQUENCY 10 TO 55 Hz, AMPLITUDE: 0.75 mm, AT 10 CYCLES FOR 3 DIRECTIONS.	AMPLI AT 10 o	VIBRATION
×	1 111 1	CONTACT RESISTANCE: NO DAMAGE, CRACK AN OF PARTS.	0 0	NSERTION		MECHANICAL OPERATION
×	INSERTION FORCE : 44.8 N MAX WITHDRAWAL FORCE : 5.6 N MIN	INSERTION FORCE : 44.8 N WITHDRAWAL FORCE : 5.6	INSE	MEASURED BY APPLICABLE CONNECTOR		INSERTION AND
×	BREAKDOWN.	NO FLASHOVER OR I	NO FLAS	300 V AC FOR 1 min.	CHAR	MECHANICAL
×		100 MΩ MIN.				RESISTANCE
×		60 mΩ MAX.	6	MAX, 1 mA(DC OR 1000Hz)	20	CONTACT RESISTANCE MILLIVOLT LEVEL METHOD
×		50 mO MAX	מט	ERISTICS 100 mA (DC OR 1000 Hz).	HACTE	ELECTRICAL CHAR
× ×	WING.	ACCORDING TO DRAWING		VISUALLY AND BY MEASURING INSTRUMENT. CONFIRMED VISUALLY.	N N	GENERAL EXAMINAT
QT AT	REQUIREMENTS	REQUIR		TEST METHOD		MELL
_			SNOI	SPECIFICATIONS	_	
	40 % TO 70 % ⁽²⁾	YTIQIN	STORAGE HUMIDITY	0.5 A	CURRENT	
	40 % TO 80 %	UMIDITY	OPERATING HUMIDITY RANGE	100 V AC	VOLTAGE	RATING
(2)	-10 °C TO 60 °C ⁽²⁾	E RANGE	STORAGE TEMPERATURE RANGE	-55 °C TO 85 °C ⁽¹⁾	OPERATING TEMPERATURE RANGE	L 5
					APPLICABLE STANDARD	APPLICABI