



TECHNICAL

LISTED: UL & CSA
 RATED SUPPLY VOLTAGE: 120VAC
 RATED CURRENT: UP TO 15 AMPS
 RESET TYPE: MANUAL
 OPERATING FREQUENCY: 60 Hz
 TYPE: CLASS A
 GROUND TRIP CURRENT: 4-6 mA
 OVERLOAD CURRENT: 90 AMP 125 VAC
 INSULATION VOLTAGE: 1,500 VRMS - 1 MINUTE
 ENDURANCE OPERATIONS: 3000 OPERATIONS
 ENVIRONMENTAL RATING: RAINPROOF RATED

MATERIAL NO.	ENGINEERING NO.	DESCRIPTION
1301530140	20053W-2	20A. IN-LINE GFCI W/PLUG & BOX
1301530143	20053W-6	20A. IN-LINE GFCI W/PLUG & BOX
1301530223	130153-0223	20A. IN-LINE GFCI BOX, NO PLUG

FUNCTIONAL SYMBOLS FA = 0 FC = 0 FD = 0	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		SCALE 1:1		CURRENT REV DESC: NEW SALES DRAWING CREATED	
	DIMENSION UNITS INCH		GENERAL TOLERANCES (UNLESS SPECIFIED)		EC NO: 690704	
DIVISIONAL SYMBOLS	ANGULAR TOL ± °		4 PLACES ±		DRWN: VBASUTHKARP 2021/12/29	
	3 PLACES ±		2 PLACES ±		CHK'D: DNGUYEN62 2022/01/24	
	2 PLACES ±		1 PLACE ±		APPR: HKNEELAND 2022/03/03	
	1 PLACE ±		0 PLACES ±		INITIAL REVISION: DRWN: VBASUTHKARP 2021/12/29 APPR: HKNEELAND 2022/03/03	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION		DRAWING SERIES D-SIZE 130153		DOCUMENT NUMBER 1301530140
				MATERIAL NUMBER SEE TABLE		DOC TYPE PSD
				CUSTOMER GENERAL MARKET		DOC PART 000
				SHEET NUMBER 1 OF 1		REVISION A