



ADVANCED CABLE TIES PART NUMBER	BUNDLE DIAMETER		A IN (mm) +/- .281 (7.137mm)	B IN (mm) +/- .005 (.127mm)	C IN (mm) +/- .010 (.254mm)	D IN (mm) +/- .020 (.508mm)	E IN (mm) +/- .020 (.508mm)	F IN (mm) +/- .030 (.762mm)	MIN LOOP TENSILE LBS (n)	ANSI/UL 94 MH FLAMABILITY RATING	PLENUM RATING
	MIN IN (mm)	MAX IN (mm)									
AP(R, L)-07-50-CW-0-C	.062 (1.57mm)	1.875 (47.625mm)	7.562 (192.075mm)	.052 (1.320mm)	.180 (4.572mm)	.300 (7.620mm)	.215 (5.461mm)	.305 (7.747mm)	50 (222)	HB	N/A
AP(R, L)-11-50-CW-0C	.062 (1.57mm)	3.062 (77.775mm)	11.250 (285.751mm)	.052 (1.320mm)	.180 (4.572mm)	.300 (7.620mm)	.215 (5.461mm)	.305 (7.747mm)	50 (222)	HB	N/A
AP(R, L)-14-50-CW-0-C	.062 (1.57mm)	4.000 (101.600mm)	14.35 (364.49mm)	.052 (1.320mm)	.180 (4.572mm)	.300 (7.620mm)	.215 (5.461mm)	.305 (7.747mm)	50 (222)	HB	N/A
AP(R, L)-14-120-CW-0-C	.187 (4.75mm)	4.0625 (103.187mm)	14.828 (376.631mm)	.076 (1.930mm)	.300 (7.620mm)	.490 (12.446mm)	.300 (7.620mm)	.500 (12.700mm)	120 (534)	HB	N/A
						COLD WEATHER SERIES CABLE TIES					
E	10/8/18	EG	DW	EG	REVISED LENGTH DIMENSION AND TOLERANCE FOR 14-120	COLOR DESIGNATIONS: 0 = UV BLACK			MATERIAL: NYLON 6/6 POLYAMIDE		
D	3/5/18	PB	EG	EG	DIMENSION A +/- FROM .125 TO .250, 14-50-CW DIMENSION A FROM 14.50 TO 14.35 AND DIMENSION C +/- FROM .005 to .010	SHEET 1 OF 1		REV.: E		DRAWING NO.: CW-D	
C	4/29/17	JA	KT	KT	NEW LOGO ADDED	DRAWN BY		DATE		CHECK	
B	2/22/17	JA	KT	KT	REVISE 14-50 LENGTH	DATE		CHECK		SCALE	
A	12/22/14	JA	KT	KT	INITIAL RELEASE	DATE		CHECK		SCALE	
REV	DATE	BY	CHK	APPROVE	DESCRIPTION	JA		4/29/17		KT	

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.
 THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.