



Product: <u>5200UH</u> ☑

Security & Sound, 2 Conductor 16 AWG, TC, Riser

Product Description

Security & Commercial Audio Cable, 2 Conductor 16 AWG stranded (19x29) tinned copper conductors with polyolefin insulation, Riser, PVC jacket with ripcord.

Technical Specifications

Product Overview

Suitable Applications:	Data Circuits, Monitor/Detection, Control Circuits, Initiating Circuits, Notification Circuits

Construction Details

Conductor

Element	No. of Elements	Size	Stranding	Material
Conductor(s)	2	16 AWG	19x29	TC - Tinned Copper

Insulation

Element	Material	Nom. Thickness	Nom. Insulation Diameter	Color Code
Conductor(s)	PP - Polypropylene	0.008 in (0.20 mm)	0.075 in (1.9 mm)	Black, Red

Outer Shield

Material No Shield

Outer Jacket

	Material	Nom. Thickness	Nom. Diameter	Ripcord
	PVC - Polyvinyl Chloride	0.017 in (0.43 mm)	0.184 in	Yes
ĺ	Overall Cable Diameter (I	Nominal): 0.184 in		

Electrical Characteristics

Electricals

Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Max. Current
4.2 Ohm/1000ft	23 pF/ft (75 pF/m)	6.25 Amps per Conductor at 25°C

Voltage

UL Voltage Rating 300 V

Mechanical Characteristics

Temperature

UL Temperature	Operating
75°C	0°C To +75°C

Bend Radius

Stationary Min.	Installation Min.
1.84 in (46.7 mm)	1.84 in
Max. Pull Tension:	: 8

Bulk Cable Weight:	23 lbs/1000ft		
--------------------	---------------	--	--

Standards and Compliance

Environmental Suitability:	Indoor - Riser, Indoor
Flammability / Reaction to Fire:	UL1666 Riser, FT4
NEC / UL Compliance:	Article 800, CMR
CEC / C(UL) Compliance:	CMG
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Plenum Number:	6200UH

History

	- 11 N 1 1 A 11 - A 11 - A 11 A 11 A 11
Update and Revision:	Revision Number: 0.241 Revision Date: 12-20-2022

Part Numbers

Variants

Item #	Color	Putup Type	Length	UPC
5200UH 0101000	Black	Reel	1,000 ft	612825157526
5200UH 010U1000	Black	UnReel	1,000 ft	612825157595
5200UH 008500	Gray	Reel	500 ft	612825157472
5200UH 008U500	Gray	UnReel	500 ft	612825157519
5200UH 0081000	Gray	Reel	1,000 ft	612825157502
5200UH 008U1000	Gray	UnReel	1,000 ft	612825157489
5200UH 009U1000	White	UnReel	1,000 ft	612825157533

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.