36 INCHES LENGTH



Connector A 132114 SMA Plug Straight Brass Gold + Heatshrink 50 Ohm RG-316 Continuity/Hi-Pot Connector B 034-5019 HD-BNC Jack Straight Bulkhead - Rear Mount Brass Nickel + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance:	132114 SMA PLUG RG174 F SMA Plug Straight Solder Standard 50 Ohm Cable	RG316 LMR100 50O	Part #: Description: Dielectric: Shielding: Diameter: Impedance:	RG-316 RG-316 - ST 0.102 ST Braid 0.102 50 Ohm	Part #: Description: Type: Gender: Body Type:	034-5019 HD-BNC BHD JK RC HD-BNC Jack Straight	G316 50O
Type: Gender: Body Type: Contact Type: Polarity:	SMA Plug Straight Solder Standard 50 Ohm	RG316 LMR100 50O	Dielectric: Shielding: Diameter: Impedance:	ST Braid 0.102	Type: Gender:	HD-BNC Jack	G316 50O
Gender: Body Type: Contact Type: Polarity:	Plug Straight Solder Standard 50 Ohm		Shielding: Diameter: Impedance:	Braid 0.102	Gender:	Jack	
Body Type: Contact Type: Polarity:	Straight Solder Standard 50 Ohm		Diameter: Impedance:	0.102			
Contact Type: Polarity:	Solder Standard 50 Ohm		Impedance:		Body Type:	Straight	
Polarity:	Standard 50 Ohm		1 ·	50 Ohm		Saugn	
-	50 Ohm		0		Contact Type:	Solder	
Impedance:			Sheathing:	None	Polarity:	Standard	
	Cable		Testing:	Continuity Hi-Pot	Impedance:	50 Ohm	
Mounting:			Length:	36 Inches	Mounting:	Bulkhead - Rear Mou	unt
Body Material:	Brass				Body Material:	Brass	
Body Finish:	Gold				Body Finish:	Nickel	
IP Rating:	None				IP Rating:	None	
Contact Material:	Brass				Contact Material:	Beryllium Copper	
Contact Finish:	Gold				Contact Finish:	Gold	
Max. Freq.:	12.4 GHz				Max. Freq.:	6 GHz	
Booting:	SMA Plug Straight				Booting:	HD-BNC Jack Straig	ht BHD
					Clocking:	0°	
mphenol		HIS DRAWING MAY CONTAIN ROPRIETARY INFORMATION 4		Title: SED SMA-ST-PL/HDBN	C-ST-JK G316 36I		UNLESS SPECIFIED TOLERANCE:
	F	OR ANY PURPOSE DETRIMEN	TAL TO CUSTOM CAI	BLE			0-18 inches +/- 1/2"
ISTOM CABLE		NC. IT MAY NOT BE REPRODU N ANY FORM WITHOUT THE W					over 18" +/- 2% ASSEMBLY:
CONTROLLED DOCUMENT - DO NOT COPY		CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.		ING Part No:			CENTER LABEL IF LENG IS LESS THAN 12 INCH



RoHS 2015/863 Compliance Statement

According to the manufacture of all the component parts contained in this assembly, this product has been determined to be RoHS Compliant with RoHS Directive 2011/65/EU and as amended by Directive 2015/863, and without material exceptions (RoHS3 Complaint).

For the individual component RoHS certificates used in this assembly, please contact Amphenol Custom Cable.

The RoHS Compliance of any product so designated is based upon evidence from the producer (manufacturers') that the component parts comply with the RoHS Directive. Amphenol Custom Cable has taken all reasonable steps to confirm that the OEM (Manufacturer) of the components used in this assembly have provided evidence regarding the absence of the restricted substances to support the manufacturer's claim of compliance.

To the best of our knowledge and with due diligence, we certify that the product listed herein complies with the RoHS requirements.

Date: 10/3/2023

Part Number: Q-3B00P0005036I

Manufacturer: Amphenol Custom Cable

Description: SMA-ST-PL/HDBNC-ST-JK G316 36I

This information is valid as of the date indicated for the item (part number) listed.

Director of Quality Assurance

Janice Frank