

ZCE1A

Limit switch head, Limit switches XC Standard,
ZCE, metal end plunger with silicone boot



The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.



Main

| | |
|---------------------------|--|
| Range of Product | Telemecanique Limit switches XC Standard |
| Series name | Standard format |
| Product or Component Type | Limit switch head |
| Device short name | ZCE |
| Head type | Plunger head |
| Product Compatibility | XCMD XCKT XCKD XCKP |

| | |
|----------------------------|--|
| Associated body | ZCT28N12 ZCMD21M12 ZCT21N12 ZCD25 ZCP29 ZCP31 ZCP26 ZCD26 ZCP21 ZCMD81L2 ZCMD81L1 ZCT25P16 ZCMD29L5 ZCP39 ZCMD39L2 ZCT26N12 ZCT25G11 ZCMD29C12 ZCMD29L2 ZCMD25L2 ZCT27N12 ZCMD41L1 ZCMD37L1 ZCD31 ZCMD81L5 ZCMD61C12 ZCMD41L2 ZCT28G11 ZCT26G11 ZCMD61M12 ZCMD21L08R12 ZCMD25L5 ZCMD25L1 ZCD21 ZCMD37L2 ZCT27G11 ZCMD29L1 ZCD37 ZCT28P16 ZCMD21L5 ZCT21P16 ZCP29M12 ZCD29M12 ZCP35 ZCD39 ZCMD69C12 ZCMD41L5 ZCMD39L5 ZCT21G11 ZCMD37L5 ZCD35 ZCP28 ZCMD21C12 ZCMD21L2 ZCMD39L1 ZCP27 ZCT26P16 ZCP37 ZCMD21L1 ZCT25N12 ZCD29 ZCP21M12 ZCP25 ZCD21M12 ZCT27P16 ZCD27 ZCD28 ZCMD21L08U78 |
| Movement of operating head | Linear |
| Type of operator | End plunger spring return metal with silicone boot) |
| Type of approach | Vertical approach, 1 direction |

Complementary

Positive opening With

Environment

| | |
|---------------------------------------|----------------------------|
| Ambient Air Temperature for Operation | -13...158 °F (-25...70 °C) |
| Ambient Air Temperature for Storage | -40...158 °F (-40...70 °C) |
| Environmental characteristic | Standard environment |

Ordering and shipping details

| | |
|-----------------------|------------------------------------|
| Category | 22413-LIMIT SWITCH, IEC, MINIATURE |
| Discount Schedule | T |
| GTIN | 3389118205307 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 0.49 oz (14.0 g) |
| Returnability | No |
| Country of origin | ID |

Packing Units

| | |
|------------------------|------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 0.79 in (2 cm) |
| Package 1 width | 1.18 in (3 cm) |
| Package 1 Length | 1.77 in (4.5 cm) |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|