



3P -20P

45	47.2	N	I19I	N	I9A	I9
42.5	44.7		I18I		I8A	I8
40	42.2		I17I		I7A	I7
32.5	34.7		I14I		I4A	I4
25	27.2		I11I		I1A	I1
17.5	19.7		I08I		I08A	I8
15	17.2		I07I		I07A	I7
12.5	14.7		I06I		I06A	I6
10	12.2		I05I		I05A	I5
7.5	9.7		I04I		I04A	I4
5	7.2	22 03	I03I	3022	I03A	I3
A	(B)	POLYBAG PACKAGE オーダー番号 ORDER NO.		MODEL NO.	極数 CKT.	

NOTES:

1. 材料 MATERIAL
 ウェハー: ポリアミド、UL94V-0 色: ナチュラル(白)
 WAFER: POLYAMIDE, UL94V-0 COLOR: NATURAL(WHITE)
 ピン: 黄銅、銅下地錫メッキ
 PIN: BRASS, TIN OVER COPPER PLATING
2. ウェハーのソリは、長さ 25.4mm に対して 0.2mm MAX.
 CAMBER MUST BE WITHIN 0.2mm MAX. PER 25.4mm
3. () 内寸法は参考値
 () REFERENCE DIMENSIONS
4. ELV 及び RoHS 適合品
 ELV AND RoHS COMPLIANT

REVISED EC NO: J2015-1182 DRINKMATSUYAMA 2015/03/17 CHKD:KASAKAWA 2015/03/19 APPR:NUKITA 2015/03/20	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE 4:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION
	0.25 UNDER	±0.03	DRAWN BY KWASHIO	DATE 2012/01/21	TITLE WAFER ASSY KK 2.5MM		
	0.25 OVER 0.5 UNDER	±0.05	CHECKED BY KASAKAWA	DATE 2013/08/13			
	1.0 OVER 10 UNDER	±0.2	APPROVED BY NUKITA	DATE 2015/03/20			
30 OVER	±0.25	MATERIAL NO. SEE CHART		DOCUMENT NO. SD-3022-001	SHEET NO. 1 OF 1		
ANGULAR	±3 °	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			