



Scan the QR code and visit the product page

Code	TK.LB.W0920.AEC	Safety level	Warning
Dimensions (H x L)	98 mm x 116 mm (3,9" x 4,6")	Version	Standard
Material	PVC base with adhesive liner and protective layer	Temperatures ⁽¹⁾	-40°C/+95°C
Applications	Machinery and control panels. Indoor and outdoor locations.		
Languages ⁽²⁾	Inglese		
Message ⁽³⁾	<p>EN: Arc Flash and Shock Hazard. Appropriate PPE Required. Do not operate controls or open covers without appropriate personal protection equipment. Failure to comply may result in injury or death. Refer to CSA Z462 for minimum PPE requirements.</p> <p>IT: Pericolo di arco elettrico e shock elettrico. DPI appropriati richiesti. Non azionare i comandi o rimuovere le protezioni senza un'adeguata protezione personale. La mancata osservanza può provocare lesioni o morte. Fare riferimento alla norma CSA Z462 per i DPI minimi richiesti.</p>		
Certifications	c(UL)us Recognized - File#MH60136 (PDGQ2, PGDQ8)		
Standards of use	ANSI Z535, OSHA Art. 1910.145, NFPA 70 (NEC), NFPA 79, UL 508A, CSA C22.1 (CECode), CSA C22.2 No.286		
Standards Construction	ANSI Z535, UL 969, CSA C22.2 No.0.15, ISO 3864, RoHS		
Standard packaging	12 pz/pcs		

(1) For indoor and outdoor exposure with high humidity or with occasional exposure to water. The minimum application temperature is +0°C. UL certification is for maximum working temperatures of +60°C.

(2) Other languages may have different sizes and available upon request.

(3) The message and the image are shown in English language only.