

# Product data sheet

Specifications



Floor standing polyester enclosure, Thalassa PLA, open bottom, ventilated canopy, 1000x1250x420mm, IP44, IK10

NSYPLAZT10124G

## Main

|                           |  |
|---------------------------|--|
| Range                     | Thalassa   |
| Product name              | Thalassa PLA   |
| Enclosure type            | Multi-purpose  |
| Product or component type | Suitable enclosure   |
| Version                   | PLAZT  |
| Nominal height            | 1000 mm  |
| Nominal width             | 1250 mm  |
| Nominal depth             | 420 mm   |
| Enclosure mounting        | Floor-standing   |
| Device composition        | 1 top part<br>1 bottom part<br>2 side part<br>2 door<br>2 rear panel<br>1 canopy<br>1 plinth |

## Complementary

|                             |  |
|-----------------------------|--|
| Body type                   | Open top and bottom part assembled with side parts                         |
| Door type                   | Plain front  |
| Number of doors             | 2 door(s)  |
| Door opening side           | Right and left (180 °)   |
| Lock type                   | 4 points lock, handle with 5 mm double bar insert                          |
| Accessibility for operation | Front<br>Bottom<br>Top<br>Rear   |
| Removable parts             | Door by hinges<br>Rear panel by fixing element<br>Canopy by fixing element |
| Material                    | Polyester reinforced with fibreglass                                       |
| Colour                      | Grey (RAL 7035)  |
| Standards                   | IEC 62208  |
| Product certifications      | Veritas  |
| Electrical insulation class | Class II   |

## Environment

|                                     |  |
|-------------------------------------|--|
| IP degree of protection             | IP44 conforming to IEC 60529 (with plinth type open bottom part and ventilated canopy) |
| IK degree of protection             | IK10 conforming to IEC 62262 (plain door)  |
| Fire resistance                     | 960 °C conforming to IEC 62208   |
| Ambient air temperature for storage | -35...90 °C  |

## Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 120.3 cm  |
| Package 1 Width              | 128.0 cm  |
| Package 1 Length             | 48.0 cm   |
| Package 1 Weight             | 66.605 kg |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)<br><a href="#">EU RoHS Declaration</a>                     |
| Mercury free               | Yes   |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a><br>Product out of China RoHS scope. Substance declaration for your information |
| RoHS exemption information | Yes   |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |

## Recommended replacement(s)