TE Internal #: 2273125-1 M12 Cable Assembly, 3 Position, .3 m, Sensor/Actuator, Code A, M12 Socket, M12 Plug, Double Ended, Plastic

View on TE.com >



Cable Assemblies > Copper Cable Assemblies > M8/M12 Cable Assemblies > M12 A-Code Male Straight to Female LED Double Ended Cable



M8/M12 Application Type: Sensor/Actuator

Number of Positions: 3

Connector & Keying Code: A

Connector Type (End A): M12 Socket
Connector Type (End B): M12 Plug

All M12 A-Code Male Straight to Female LED Double Ended Cable (60)

#### **Features**

#### **Product Type Features**

Connector Type (End A)	M12 Socket
Connector Type (End B)	M12 Plug
Cable Assembly Type	M12
Configuration Features	
Status Indicator Type	LED
Number of Positions	3
Electrical Characteristics	
Operating Voltage	24 VDC
Body Features	
Cable Color	Black
Connector Color (End B)	Black
Connector Color (End A)	Black
Jacket Material	PUR



Wire Color (Base) Connector & Keying Code Contact Features  Contact Current Rating (Max)  Mechanical Attachment  Thread Size Connector Orientation (End A) Connector Orientation (End B)  Housing Features  Housing Material  Plastic  Dimensions  Outside Cable Diameter Wire Size  Usage Conditions  Operating Temperature Range  A8 Brown, Blue, Black  A  A  A  A  A  A  A  Mechanical Attachment  M12 x M12  Right Angle  Straight  Plastic  Dimensions  Outside Cable Diameter  4.3 mm[.161 in]  Wire Size  Jaze Conditions  Operating Temperature Range  A9 - 80 °C[.40 - 176 °F]  Operation/Application  M8/M12 Application Type Sensor/Actuator  Shielded No  Packaging Features
Contact Current Rating (Max) 4 A  Mechanical Attachment  Thread Size M12 x M12  Connector Orientation (End A) Right Angle  Connector Orientation (End B) Straight  Housing Features  Housing Material Plastic  Dimensions  Outside Cable Diameter 4.3 mm[.161 in]  Wire Size .326 mm²  Usage Conditions  Operating Temperature Range -40 - 80 °C[-40 - 176 °F]  Operation/Application  M8/M12 Application Type Sensor/Actuator  Shielded No
Contact Current Rating (Max)  Mechanical Attachment  Thread Size M12 x M12  Connector Orientation (End A) Right Angle  Connector Orientation (End B) Straight  Housing Features  Housing Material Plastic  Dimensions  Outside Cable Diameter 4.3 mm[.161 in]  Wire Size .326 mm²  Usage Conditions  Operating Temperature Range -40 - 80 °C[-40 - 176 °F]  Operation/Application  M8/M12 Application Type Sensor/Actuator  Shielded No
Mechanical Attachment  Thread Size M12 x M12  Connector Orientation (End A) Right Angle  Connector Orientation (End B) Straight  Housing Features  Housing Material Plastic  Dimensions  Outside Cable Diameter 4.3 mm[.161 in]  Wire Size .326 mm²  Usage Conditions  Operating Temperature Range -40 - 80 °C[-40 - 176 °F]  Operation/Application  M8/M12 Application Type Sensor/Actuator  Shielded No
Thread Size M12 x M12  Connector Orientation (End A) Right Angle  Connector Orientation (End B) Straight  Housing Features  Housing Material Plastic  Dimensions  Outside Cable Diameter 4.3 mm[.161 in]  Wire Size .326 mm²  Usage Conditions  Operating Temperature Range -40 - 80 °C[-40 - 176 °F]  Operation/Application  M8/M12 Application Type Sensor/Actuator  Shielded No
Connector Orientation (End A)  Connector Orientation (End B)  Straight  Housing Features  Housing Material  Plastic  Dimensions  Outside Cable Diameter  4.3 mm[.161 in]  Wire Size  Jage Conditions  Operating Temperature Range  Operation/Application  M8/M12 Application Type  Sensor/Actuator  Shielded  Straight  Right Angle  Straight  Angle  Straight  Algerian  Plastic  Plastic  -4.3 mm[.161 in]  4.3 mm[.161 in]  Sensor/Actuator  No
Connector Orientation (End B)  Housing Features  Housing Material  Plastic  Dimensions  Outside Cable Diameter  4.3 mm[.161 in]  Wire Size  Jack mm²  Usage Conditions  Operating Temperature Range  M8/M12 Application Type  Sensor/Actuator  No
Housing Features  Housing Material Plastic  Dimensions  Outside Cable Diameter 4.3 mm[.161 in]  Wire Size .326 mm²  Usage Conditions  Operating Temperature Range -40 – 80 °C[-40 – 176 °F]  Operation/Application  M8/M12 Application Type Sensor/Actuator  Shielded No
Housing Material Plastic  Dimensions  Outside Cable Diameter 4.3 mm[.161 in]  Wire Size .326 mm²  Usage Conditions  Operating Temperature Range -40 – 80 °C[-40 – 176 °F]  Operation/Application  M8/M12 Application Type Sensor/Actuator  Shielded No
Dimensions  Outside Cable Diameter 4.3 mm[.161 in]  Wire Size .326 mm²  Usage Conditions  Operating Temperature Range -40 – 80 °C[-40 – 176 °F]  Operation/Application  M8/M12 Application Type Sensor/Actuator  Shielded No
Outside Cable Diameter 4.3 mm[.161 in]  Wire Size .326 mm²  Usage Conditions  Operating Temperature Range -40 – 80 °C[-40 – 176 °F]  Operation/Application  M8/M12 Application Type Sensor/Actuator  Shielded No
Wire Size .326 mm²  Usage Conditions  Operating Temperature Range -40 - 80 °C[-40 - 176 °F]  Operation/Application  M8/M12 Application Type Sensor/Actuator  Shielded No
Usage Conditions  Operating Temperature Range -40 – 80 °C[-40 – 176 °F]  Operation/Application  M8/M12 Application Type Sensor/Actuator  Shielded No
Operating Temperature Range -40 – 80 °C[-40 – 176 °F]  Operation/Application  M8/M12 Application Type Sensor/Actuator  Shielded No
Operation/Application  M8/M12 Application Type  Sensor/Actuator  No
M8/M12 Application Type  Sensor/Actuator  Shielded  No
Shielded
Packaging Features
Packaging Quantity 25
Packaging Method Box
Other
Field Serviceable Yes
Cable Assembly Length .3 m
Cable Assembly Configuration  Double Ended

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	



Current ECHA Candidate List: JUNE 2023

(235)

Candidate List Declared Against: JAN 2022

(223)

Does not contain REACH SVHC

Halogen Content

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC

Free

Solder Process Capability

Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**



# Customers Also Bought



















#### **Documents**

#### **Product Drawings**

M12 angld sckt to M12 strght plg 2 LED

English

#### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_2273125-1\_A.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2273125-1\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2273125-1\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

### Datasheets & Catalog Pages

M8 / M12 Connector System Catalog

English

M8 / M12 Connector System Catalog

Japanese

## **Product Specifications**

**Product Specification** 

English