

## Printed-circuit board connector - PC 4/ 4-GU-7,62 - 1883789

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Header, Nominal current: 20 A, Rated voltage (III/2): 630 V, Number of positions: 4, Pitch: 7.62 mm, Color: green, Contact surface: Tin, Assembly: Soldering

### Key commercial data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 pc     |
| Weight per Piece (excluding packing) | 8.61 GRM |
| Custom tariff number                 | 85366990 |
| Country of origin                    | Germany  |

### Technical data

#### Dimensions

|                |            |
|----------------|------------|
| Pitch          | 7.62 mm    |
| Dimension a    | 22.86 mm   |
| Pin dimensions | 1 x 0,8 mm |

#### General

|                                |            |
|--------------------------------|------------|
| Range of articles              | PC 4/..-GU |
| Rated surge voltage (III/3)    | 6 kV       |
| Rated surge voltage (III/2)    | 6 kV       |
| Rated surge voltage (II/2)     | 6 kV       |
| Rated voltage (III/3)          | 400 V      |
| Rated voltage (III/2)          | 630 V      |
| Rated voltage (II/2)           | 630 V      |
| Nominal current I <sub>N</sub> | 20 A       |
| Color                          | green      |
| Number of positions            | 4          |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 272607xx |
| eCl@ss 4.1 | 27260701 |
| eCl@ss 5.0 | 27260701 |
| eCl@ss 5.1 | 27260701 |
| eCl@ss 6.0 | 27260704 |

# Printed-circuit board connector - PC 4/ 4-GU-7,62 - 1883789

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 7.0 | 27440402 |
| eCl@ss 8.0 | 27440402 |

### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC001121 |
| ETIM 4.0 | EC002637 |
| ETIM 5.0 | EC002637 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211810 |
| UNSPSC 7.0901 | 39121409 |
| UNSPSC 11     | 39121409 |
| UNSPSC 12.01  | 39121409 |
| UNSPSC 13.2   | 39121409 |

## Approvals

### Approvals

---

#### Approvals

UL Recognized / cUL Recognized / GOST / cULus Recognized

---


#### Ex Approvals

---

#### Approvals submitted


---

## Approval details

|   |       |       |
|---|-------|-------|
| UL Recognized  |       |       |
|   | B     | C     |
| Nominal current I <sub>N</sub>  | 20 A  | 20 A  |
| Nominal voltage U <sub>N</sub>  | 300 V | 300 V |

# Printed-circuit board connector - PC 4/ 4-GU-7,62 - 1883789

## Approvals

cUL Recognized 

|                                | B     | C     |
|--------------------------------|-------|-------|
| Nominal current I <sub>N</sub> | 20 A  | 20 A  |
| Nominal voltage U <sub>N</sub> | 300 V | 300 V |

GOST 

cULus Recognized 