# NSYS3D6830P

Spacial S3D plain door with mount.plate. H600xW800xD300.IP66 IK10 RAL7035.





#### Main

Spacial
Spacial S3D
Multi-purpose
Compact enclosure
23.62 in (600 mm)
31.50 in (800 mm)
11.81 in (300 mm)
Solid
Plain
Standard
Wall-mounting
1 body 2 cable gland plate 1 mounting plate 1 door with lock

#### Complementary

Body type	Single piece body Gutter-shaped front rail double sheet thickness	
Number of doors	Front face 1	
Door opening side	Reversible 120 °)	
Lock type	3 points lock, 3 mm double-bar	
Accessibility for operation	Front	
Removable parts	Door by hinges Cable gland plate by screws Mounting plate by fixing element	
Material	Enclosure steel Mounting plate galvanised steel	
Surface finish	Enclosure epoxy-polyester powder	
Color	Enclosure Gray RAL 7035)	
Standards	IEC 62208	
Product Certifications	UL BV LR CUL DNV GL	
Net Weight	72.75 lb(US) (33 kg)	

### Environment

NEMA Degree of Protection	NEMA 4X/13
IK degree of protection	IK10 IEC 62262
IP degree of protection	IP66 IEC 60529

# Ordering and shipping details

Category	80034-ENCLOSURE SYSTEMS WALL MOUNT METAL
Discount Schedule	ES1
GTIN	3606480159114
Nbr. of units in pkg.	1
Package weight(Lbs)	72.75 lb(US) (33.0 kg)
Returnability	No
Country of origin	FR

# Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	24.33 in (61.8 cm)	
Package 1 width	32.01 in (81.3 cm)	
Package 1 Length	13.70 in (34.8 cm)	

### Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
RoHS exemption information	₽¥Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

### Contractual warranty

Warranty	18 months	