

# FOC-OP12-OP12-GL02/60 - Connecting cable



1415230

<https://www.phoenixcontact.com/us/products/1415230>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Double-end preassembled cable, type: circular connector, degree of protection: IP68, number of positions: 12

## Product description

Robust connecting cable Q-ODC-12 to Q-ODC-12, push-pull interlocking, degree of protection: IP68

## Your advantages

- Compact design with MT ferrule
- Push-pull interlocking
- For extreme ambient conditions

## Commercial data

Item number	1415230
Packing unit	1 pc
Minimum order quantity	10 pc
Note	Made to order (non-returnable)
Sales key	AB15
Product key	ABNHAA
GTIN	4055626045740
Weight per piece (including packing)	3,315 g
Weight per piece (excluding packing)	3,245 g
Customs tariff number	85447000
Country of origin	PL

1415230

<https://www.phoenixcontact.com/us/products/1415230>

## Technical data

### Product properties

Product type	Data cable preassembled
Sensor type	Ethernet
Number of positions	12

### Electrical properties

Attenuation	typ. 0.2 dB
	max. 0.6 dB
Transmission medium	Multi-mode fiberglass

### Mechanical properties

Tensile strength short-term/long-term	500 N
---------------------------------------	-------

### Material specifications

Flammability rating according to UL 94	V0
Outer sheath, material	LSFH

### Connector

#### Connection 1

Handle color	black
Insertion/withdrawal cycles	500 (In the event of repeated cleaning)
Degree of protection	IP68 (IEC 60529)
	IP68
Ambient temperature (operation)	-40 °C ... 85 °C (IEC 61300-2-22)
Number of positions	12
Insertion/withdrawal cycles	500
Locking type	Push Pull

#### Connection 2

Handle color	black
Insertion/withdrawal cycles	500 (In the event of repeated cleaning)
Ambient temperature (operation)	-40 °C ... 85 °C (IEC 61300-2-22)
Number of positions	12
Degree of protection	IP68 (IEC 60529)
Locking type	Push Pull

### Cable/line

Cable length	60 m
Cable weight	55.00 kg/km
Cable type	Multimode fiberglass
Cable type	Zip cord, fiberglass
Cable abbreviation	12-.../H(ZNG)H-...70

# FOC-OP12-OP12-GL02/60 - Connecting cable



1415230

<https://www.phoenixcontact.com/us/products/1415230>

External cable diameter	7 mm
Outer sheath, material	LSFH
External sheath, color	black
Wire diameter incl. insulation	250 µm
Individual wire diameter	250 µm
Smallest bending radius, fixed installation	≥ 70 mm
Tensile strength short-term/long-term	500 N
Lateral pressure short term	500.00 N/cm
Lateral pressure, long-term	200.00 N/cm
Halogen-free	complying with IEC 60754-1/2

## FO cable

Number of fibers	12
Fiber	62.5/125 µm OM1
Fiber type	Multimode fiberglass 62.5/125 µm
Attenuation	typ. 0.15 dB
Transmission medium	Multi-mode fiberglass

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP68
Ambient temperature (operation)	-40 °C ... 85 °C (IEC 61300-2-22)
Shock	50g, in accordance with IEC 61300-2-9

# FOC-OP12-OP12-GL02/60 - Connecting cable



1415230

<https://www.phoenixcontact.com/us/products/1415230>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1415230>



**EAC**

Approval ID: 19060508

1415230

<https://www.phoenixcontact.com/us/products/1415230>

## Classifications

### ECLASS

ECLASS-11.0	27440312
ECLASS-13.0	27440312
ECLASS-12.0	27440312

### ETIM

ETIM 8.0	EC002641
----------	----------

### UNSPSC

UNSPSC 21.0	39121400
-------------	----------

# FOC-OP12-OP12-GL02/60 - Connecting cable



1415230

<https://www.phoenixcontact.com/us/products/1415230>

## Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

# FOC-OP12-OP12-GL02/60 - Connecting cable



1415230

<https://www.phoenixcontact.com/us/products/1415230>

## Accessories

### FOC-MODUL:3U-OS12-LCD6-OM1 - Module

1419978

<https://www.phoenixcontact.com/us/products/1419978>



1\*12-insert 3U module, type: 19"-rack mount patch module, degree of protection: IP20, number of positions: 1\*12, marking material: aluminum, color: gray

---

Phoenix Contact 2023 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)