ATGBICS FWLF-1521-7D-49 Finisar Compatible Transceiver CWDM SFP 2.67Base (1491nm, SMF, LC, DOM)

Brand : ATGBICS

Product code: FWLF-1521-7D-49-C

Product name : FWLF-1521-7D-49 Finisar Compatible Transceiver CWDM SFP 2.67Base (1491nm, SMF, LC, DOM)

FWLF-1521-7D-49 Finisar Compatible Transceiver CWDM SFP 2.67Base (1491nm, SMF, LC, DOM) ATGBICS FWLF-1521-7D-49 Finisar Compatible Transceiver CWDM SFP 2.67Base (1491nm, SMF, LC, DOM). SFP transceiver type: Fiber optic, Maximum data transfer rate: 2670 Mbit/s, Interface type: SFP. Product colour: Silver, Housing material: Metal, Country of origin: United Kingdom. Input voltage: 3.3 V, Maximum voltage: 3.5 V, Power consumption (typical): 1 W. Width: 13.4 mm, Depth: 56.5 mm, Height: 8.5 mm. Number of products included: 1 pc(s), Package type: Box

Performance

SFP transceiver type *	Fiber optic
Maximum data transfer rate *	2670 Mbit/s
Interface type *	SFP
Single-mode fiber (SMF) supported	✔
Multi-mode fiber (MMF) supported	✘
Fiber optic connector	LC
SFP transceiver standard	CWDM
Wavelength	1491 nm
Coarse Wavelength Division Multiplexing (CWDM)	✔
Ethernet LAN	✔
Ethernet interface type	2.5 Gigabit Ethernet
Digital Diagnostics Monitoring (DDM)	✔

Features

Product colour	Silver
Housing material	Metal
Plug and Play	✔
Hot-swap	✔
Easy to install	✔
Country of origin	United Kingdom
Brand compatibility	Finisar
Certification	CE, FCC, RoHS

Power

Input voltage	3.3 V
Maximum voltage	3.5 V
Power consumption (typical)	1 W

Operational conditions

Maximum operating temperature	70 °C
Operating temperature (T-T)	0 - 70 °C
Storage temperature (T-T)	-40 - 85 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%

Weight & dimensions

Width	13.4 mm
Depth	56.5 mm
Height	8.5 mm
Weight	15 g

Packaging data

Number of products included	1 pc(s)
Package type	Box

Technical details

Sustainability compliance	✔
Sustainability certificates	RoHS
Doesn't contain	Lead

5056468767776