

In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD		TEST METHOD		REQUIREMENTS		Q	AT	
RATING	OPERATING TEMPERATURE RANGE	-55 °C TO 85 °C (1)	STORAGE TEMPERATURE RANGE	-10 °C TO 60 °C (2)				
	VOLTAGE	100 V AC	OPERATING HUMIDITY RANGE	40 % TO 80 %				
	CURRENT	0.5 A	STORAGE HUMIDITY RANGE	40 % TO 70 % (2)				
SPECIFICATIONS								
ITEM	TEST METHOD		REQUIREMENTS		Q	AT		
CONSTRUCTION		VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.		X	X	
GENERAL EXAMINATION		CONFIRMED VISUALLY.				X	X	
ELECTRIC CHARACTERISTICS								
CONTACT RESISTANCE	100 mA (DC OR 1000 Hz).	40 mΩ MAX.			X		-	
CONTACT RESISTANCE	20 mV MAX, 1 mA(DC OR 1000Hz)	50 mΩ MAX.			X		-	
MILLIVOLT LEVEL METHOD								
INSULATION RESISTANCE	250 V DC	100 MΩ MIN.			X		-	
VOLTAGE PROOF	300 V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.			X		-	
MECHANICAL CHARACTERISTICS								
INSERTION AND WITHDRAWAL FORCES	MEASURED BY APPLICABLE CONNECTOR.	INSERTION FORCE : 88.0 N MAX. WITHDRAWAL FORCE : 10.0 N MIN.			X		-	
MECHANICAL OPERATION	100 TIMES INSERTIONS AND EXTRACTIONS.	① CONTACT RESISTANCE: 50 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.			X		-	
VIBRATION	FREQUENCY 10 TO 55 Hz. AMPLITUDE : 1.5 mm, AT 2h FOR 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.			X		-	
SHOCK	490 ms ² , DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.				X		-	
ENVIRONMENTAL CHARACTERISTICS								
DAMP HEAT (STEADY STATE)	EXPOSED AT 40±2 °c, 90 ~ 95 %, 96 h.	① CONTACT RESISTANCE: 50 mΩ MAX. ② INSULATION RESISTANCE: 100 MΩ MIN.			X		-	
RAPID CHANGE OF TEMPERATURE	TEMPERATURE: 55 → +15 ~ +35 → +85 → +15 ~ +35 °c TIME 30 → MAX 5 → 30 → MAX 5 min UNDER 5 CYCLES.	③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.			X		-	
CORROSION SALT MIST	EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.	① CONTACT RESISTANCE: 50 mΩ MAX. ② NO HEAVY CORROSION.			X		-	
HYDROGEN SULPHIDE	EXPOSED IN 3 PPM FOR 96 h. (TEST STANDARD: JEIDA 38)				X		-	
RESISTANCE TO SOLDERING HEAT	1) REFLOW SOLDERING : 250 °c MAX, : 220 °c MIN, FOR 60 s 2) SOLDERING IRONS : 360 °c, FOR 5 s	NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.			X		-	
SOLDERABILITY	SOLDERED AT SOLDER TEMPERATURE, 240 ± 3 °c, FOR IMMERSION DURATION, 3 s.	A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMERSERD.			X		-	
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE				
△								
REMARK ① TEMPERATURE RISE INCLUDED WHEN ENERGIZED. ② THIS STORAGE INDICATES A LONG-TERM STORAGE STATE FOR THE UNUSED PRODUCT BEFORE THE BOARD MOUNTED. Unless otherwise specified, refer to MIL-STD-1344.								
Note QT: Qualification Test AT: Assurance Test X: Applicable Test		DRAWING NO.		ELG4-071337-21				
HRS		SPECIFICATION SHEET		PART NO.		FX6A-100S-0.8SV (91)		
		HIROSE ELECTRIC CO., LTD.		CODE NO.		GL576-0308-6-91		
				APPROVED		HS. OKAWA		06.10.10
				CHECKED		HS. OZAWA		06.10.10
		DESIGNED		KT. 001		06.10.05		
		DRAWN		KT. 001		06.10.05		