# **BGA Heat Sink - High Performance Straight Fin w/Thermal Tape**





ATS Part#: **ATS-54400K-C1-R0** 

Description: 40.00 x 40.00 x 14.50 mm BGA Heat Sink - High Performance Straight Fin

w/Thermal Tape

Heat Sink Type: Straight Fin
Heat Sink Attachment: Thermal Tape

Equivalent Part Number: ATS-54400K-C2-R0


#### **Features & Benefits**

- High aspect ratio, straight fin heat sinks that are ideal for compact PCB environments
- · Designed specifically for BGAs and other surface mount packages
- · Comes preassembled with high performance thermal interface material

### **Thermal Performance**

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	4.6 °C/W	3.3 °C/W	2.8 °C/W	2.5 °C/W	2.2 °C/W	2.1 °C/W	1.9 °C/W
	Ducted Flow	2.4	N/A	N/A	N/A	N/A	N/A	N/A

## **Product Detail**



Dimension A	Dimension B	Dimension C	Dimension D	TIM	Finish
40.00 mm	40.00 mm	14.50 mm	N/A mm	T412	BLACK-ANODIZED

#### Notes:

- Dimension A and B refer to component size.
- Dimension C is the heat sink height from the bottom of the base to the top of the fin field.
- ATS-54400K-C2-R0 is the exact heat sink assembly with an equivalent thermal interface material (Saint-Gobain C675).
- Thermal performance data are provided for reference only. Actual performance may vary by application.
- ATS reserves the right to update or change its products without notice to improve the design or performance.
- ATS certifies that this heat sink assembly is RoHS-6 and REACH compliant.
- Contact ATS to learn about custom options available.



<sup>\*</sup>Image above is for illustration purpose only.