Data sheet







Insulated cross-connector, No. of poles: 2, Mounting type: Plug in, Width: 9.6 mm, Colour: Yellow

RAL: 1026

Business data

Article number	17402.8	
Article name	FIQI 2,5-4/2 YE	
GTIN (EAN)	4044211175955	
Packaging unit	50	
Quantity unit	PC	
Weight per piece (not including packaging)	1.2 g	
Weight per piece (including packaging)	1.23 g	
Unit of weight	G	
Customs number	85389099	
Country of origin	DE	
Product description	Insulated cross-connector	
Colour	Yellow	

Data sheet





Technical data	
Dimensions	
Length	3.4 mm
Width	9.6 mm
Pitch size	5.1 mm
Ratings	
Max. voltage	800 V
Rated current	24 A
Current load, max.	32 A
Rated cross-section	2.5 mm ²
Contamination degree	2
Connection data	
No. of poles	2
Materials	
Material	Bronze
Insulation housing	Polyamide 6.6
Flammability class UL 94	V-2
Working temperature, min.	-40 °C
Working temperature, max.	105 °C
Further technical data	
Mounting type	Plug in
Insulation available	✓
Touch protection is available	✓
Number of bridged terminals	2
Environmental Product Compliance	
REACH Conform	yes
REACH Reference date	2023-01-17
REACH Candidate Substance Note	No
RoHS Conform	yes

Data sheet 17402.8 FIQI 2,5-4/2 YE



Media

Data sheet





Accessories

##INVERSE##CONTA-CONNECT



Neutral-disconnect terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 5.1 mm, Colour: Blue

Article number	Article name	GTIN (EAN)	Packaging unit
3273.5	FNT 2,5-4 BU	4044211138974	100 ST



Feed-through installation terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3276.2	FRKI 2,5-4 BG	4044211139001	100