

HCK Series Specifications

MECHANICAL	
ANGLE OF MOVEMENT	90° (45° EACH DIRECTION)
EXPECTED CYCLE LIFE	5 MILLION
CENTERING	SPRING RETURN
MATERIAL	GLASS/MINERAL FILLED NYLON
BREAK OUT TORQUE	0.13 lbFin
MAX. ALLOWABLE TORQUE	50 lbFin

MOLEX 510210400 CONNECTOR		
PIN #	WIRE COLOR	DESCRIPTION
1	N/A	N/A
2	YELLOW	SENSOR
3	BLACK	GROUND
4	RED	POWER (+5V)

ELECTRICAL	
SENSOR TYPE	HALL EFFECT
RESOLUTION	12 BIT
SUPPLY VOLTAGE	5VDC ± 0.01VDC
OUTPUT VOLTAGE	SEE OPTIONS
RETURN TO CENTER VOLTAGE	± 50mV
OVERVOLTAGE MAX.	20VDC
REVERSE POLARITY MAX.	-10VDC

ENVIRONMENTAL	
OPERATING TEMPERATURE	-10°F TO 185°F
STORAGE TEMPERATURE	-40°F TO 185°F
IP SEALING ABOVE PANEL	IP67
EMC IMMUNITY LEVEL	EN61000-4-3 *Compliance to 30A/m
EMC EMISSIONS LEVEL	EN61000-6-3
ESD IMMUNITY LEVEL	EN61000-4-2 *Compliance to ±15kV/±8kV
VIBRATION TESTING	Per SAE J1455 Section 4.9 & MIL-STD810G 514.6
MECHANICAL SHOCK	Per SAE J1455 Section 4.10 & MIL-STD-202G



10" CABLE PROVIDED

IP RATING: IP67 ABOVE PANEL

*Extended Testing Levels