FIS 8RU RACK MOUNT ENCLOSURE





FEATURES

- (2) Slide Out Trays with Spring Loaded Stop Latch
- Holds (24) LGX Adapter Plates, Cassettes, or Modules
- Built In Raised Splice Tray Mounting Bracket
- Multiple Tie Downs and Cable Retention Brackets
- Hinged Front and Rear Removable Doors, Lexan Doors Available
- Order Preloaded with Terminated Cables, Adapters, Pigtails or Cassettes
- Rugged 14 Gauge Aluminum, Available in Black or Off-White (BW)

The 8RU FIS Rack Mount Enclosure provides many flexible configurations in an 8RU form factor. It accommodates either (24) LGX adapter plates, modules or cassettes depending on the style chosen. Slide out trays and removable front and back doors allow easy access to the patch bay. Multiple cable retention brackets and tie down spots allow for convenient cable management. Spring loaded stop latches keep the tray securely in place when retracted. Rack mount installs into a standard 19" rack. Adapter plates, 23" mounting brackets and 19" flush mounting brackets are sold separately.


SPECIFICATIONS


SPECIFICATIONS	
Dimensions	17"W x 14"D x 14"H
Capacity	Up to 144 (6 Pack) or 192 (8 Pack) Simplex Connections
	Up to 288 (6 Pack) Duplex Connections (LC or SC)
Material	.060" Aluminum
Coatings	Flectro-statically Applied Powder Coat, Available in Black or Off White


FIS 8RU RACK MOUNT ENCLOSURE



TECH DRAWING







ORDERING INFORMATION

F1RM8RU24X	8RU Rack Mount, 24 Plates, Solid Front/Rear Doors, Black
F1RM8RU24XL	8RU Rack Mount, 24 Plates, Smoked Lexan Front and Solid Rear Door, Black
F1RM8RU24X-BW	8RU Rack Mount, 24 Plates, Solid Front/Rear Doors, Off White
F1RM8RU24XL-BW	8RU Rack Mount, 24 Plates, Smoked Lexan Front and Solid Rear Door, Off White

ACCESSORIES (PURCHASED SEPARATELY)

4RURACK-ADP23	4RU and 8RU 23" Rack Mounting Brackets, Pair, Black
4RURACK-ADP23BW	4RU and 8RU 23" Rack Mounting Brackets, Pair, Off White
F1-SPL12	Metal Splice Tray, 12 Position Fusion Splice Chip, 6.5″L x 4.7″W x .42″H
F1-SPL24	Metal Splice Tray, 24 Position Fusion Splice Chip, 11.72"L x 3.99"W x .42"H
F1-6808	Plastic Splice Tray, 12 Position Fusion Splice Chip, 7.1"L x 4.25"W x .48"H
F1-6707BLKF	Metal Splice Tray, 12 Position Fusion Splice Chip, 7.5° L x 4° W x $.63^{\circ}$ H
F1-13189	Cable Retention Rings For 4RU & 8RU Interconnect - 10 pack