

OSRAM SFH 7016

Datasheet

Published by **ams-OSRAM AG**

Tobelbader Strasse 30, 8141 Premstaetten, Austria

Phone +43 3136 500-0

ams-osram.com


© All rights reserved



Multi Chip LED

SFH 7016

Green (530 nm), Red (655 nm) and
Infrared (940 nm) Emitter



Applications

- Health Monitoring (Heart Rate Monitoring, Pulse Oximetry)

Features

- Package: clear silicone
- ESD: 2 kV acc. to ANSI/ESDA/JEDEC JS-001 (HBM, Class 2)
- SMT package
- Suitable for SMT assembly
- Available on tape and reel
- Emitters can be controlled separately

Ordering Information

| Type | Brightness ¹⁾²⁾ | Ordering Code |
|--------------|---|---------------|
| SFH 7016 | | Q65112A7849 |
| ● true green | ● $I_e = 2.20 \dots 5.40 \text{ mW/sr}$ ($I_F = 20 \text{ mA}$) | |
| ● hyper red | ● $I_e = 2.50 \dots 7.00 \text{ mW/sr}$ ($I_F = 20 \text{ mA}$) | |

Ordering Information

| Type | Brightness ¹⁾²⁾ | Ordering Code |
|---------------------|---|---------------|
| • infrared (940 nm) | • $I_e = 1.65 \dots 4.05 \text{ mW/sr}$ ($I_F = 20 \text{ mA}$) | |

Maximum Ratings

$T_s = 25\text{ °C}$

| Parameter | Symbol | | Values | Values | Values |
|---|----------------|------|--------------|-------------|------------------------|
| | | | ● true green | ● hyper red | ● infrared (940 nm) |
| Operating temperature | T_{op} | min. | -40 °C | -40 °C | -40 °C |
| | | max. | 85 °C | 85 °C | 85 °C |
| Storage temperature | T_{stg} | min. | -40 °C | -40 °C | -40 °C |
| | | max. | 85 °C | 85 °C | 85 °C |
| Junction temperature | T_j | max. | 100 °C | 100 °C | 100 °C |
| Forward current | I_F | max. | 30 mA | 40 mA | 60 mA |
| Forward current pulsed $t_p \leq 50\text{ }\mu\text{s}$ (G); $t_p \leq 900\text{ }\mu\text{s}$ (R); $t_p \leq 60\text{ }\mu\text{s}$ (IR); $D \leq 0.005$ | $I_{F\ pulse}$ | max. | 0.75 A | 0.3 A | 1 A |
| Reverse voltage ³⁾ | V_R | max. | 5 V | 5 V | 5 V |
| Power consumption | P_{tot} | max. | 90 mW | 100 mW | 110 mW |
| ESD withstand voltage acc. to ANSI/ESDA/JEDEC JS-001 (HBM, Class 2) | V_{ESD} | max. | 2 kV | 2 kV | 2 kV |

The stated maximum ratings refer to one chip, unless otherwise specified.


Characteristics

$I_F = 20 \text{ mA}$; $t_p = 20 \text{ ms}$; $T_S = 25 \text{ °C}$

| Parameter | Symbol | | Values | Values | Values |
|--|-----------------------------|------|-------------------|-------------------|---------------------|
| | | | ● true green | ● hyper red | ● infrared (940 nm) |
| Peak wavelength | λ_{peak} | typ. | 526.0 nm | 660.0 nm | 950.0 nm |
| Centroid wavelength ⁴⁾ | $\lambda_{\text{centroid}}$ | min. | 522.5 nm | 652.5 nm | 930.5 nm |
| | | typ. | 530.0 nm | 655.0 nm | 940.0 nm |
| | | max. | 541.5 nm | 657.5 nm | 949.5 nm |
| Spectral bandwidth at 50% $I_{\text{rel,max}}$ (FWHM) | $\Delta\lambda$ | typ. | 32.0 nm | 17.0 nm | 42.0 nm |
| Half angle | φ | typ. | 60 ° | 60 ° | 60 ° |
| Dimensions of active chip area | L x W | typ. | 0.5 x 0.5 mm x mm | 0.3 x 0.3 mm x mm | 0.3 x 0.3 mm x mm |
| Rise time (10% / 90%) $I_F = 100 \text{ mA}$; $R_L = 50 \text{ }\Omega$ | t_r | typ. | 59 ns | 17 ns | 16 ns |
| Fall time (10% / 90%) $I_F = 100 \text{ mA}$; $R_L = 50 \text{ }\Omega$ | t_f | typ. | 59 ns | 17 ns | 16 ns |
| Forward voltage ⁵⁾ | V_F | min. | 2.20 V | 1.70 V | 1.10 V |
| | | typ. | 2.40 V | 1.90 V | 1.30 V |
| | | max. | 2.80 V | 2.20 V | 1.50 V |
| Reverse current ³⁾ $V_R = 5 \text{ V}$ | I_R | max. | 10 μA | 10 μA | 10 μA |
| Radiant intensity ¹⁾²⁾ $I_F = 20 \text{ mA}$; $t_p = 20 \text{ ms}$ | I_e | min. | 2.2 mW/sr | 2.5 mW/sr | 1.65 mW/sr |
| | | typ. | 4 mW/sr | 4.2 mW/sr | 3 mW/sr |
| | | max. | 5.4 mW/sr | 7 mW/sr | 4.05 mW/sr |
| Total radiant flux ⁶⁾ | Φ_e | typ. | 14 mW | 14 mW | 11 mW |
| Temperature coefficient of voltage | TC_V | typ. | -3.6 mV / K | -1.7 mV / K | -0.8 mV / K |
| Temperature coefficient of brightness | TC_I | typ. | -0.35 % / K | -0.7 % / K | -0.3 % / K |
| Temperature coefficient of wave-length | TC_λ | typ. | 0.03 nm / K | 0.18 nm / K | 0.3 nm / K |
| Thermal resistance junction solder point real ⁷⁾ | $R_{\text{thJS real}}$ | typ. | 210 K / W | 260 K / W | 320 K / W |
| | | max. | 260 K / W | 310 K / W | 380 K / W |


Relative Spectral Emission 8), 9)

- true green: $I_{e,rel} = f(\lambda)$; $I_F = 20 \text{ mA}$; $t_p = 20 \text{ ms}$




Relative Spectral Emission 8), 9)

- hyper red: $I_{e,rel} = f(\lambda)$; $I_F = 20 \text{ mA}$; $t_p = 20 \text{ ms}$




Relative Spectral Emission ^{8), 9)}

- infrared (940 nm): $I_{e,rel} = f(\lambda)$; $I_F = 20 \text{ mA}$; $t_p = 20 \text{ ms}$




Radiation Characteristics ^{8), 9)}

$I_{rel} = f(\phi)$; $T_S = 25 \text{ }^\circ\text{C}$




Forward current 8), 9)

- true green: $I_F = f(V_F)$; single pulse; $t_p = 100 \mu s$




Forward current 8), 9)

- hyper red: $I_F = f(V_F)$; single pulse; $t_p = 100 \mu s$




Forward current 8), 9)

- infrared (940 nm): $I_F = f(V_F)$; single pulse; $t_p = 100 \mu s$




Relative Radiant Intensity ^{8), 9)}

• true green: $I_e/I_e(20\text{mA}) = f(I_F)$; single pulse; $t_p = 25 \mu\text{s}$




Relative Radiant Intensity ^{8), 9)}

• hyper red: $I_e/I_e(20\text{mA}) = f(I_F)$; single pulse; $t_p = 100 \mu\text{s}$




Relative Radiant Intensity ^{8), 9)}

• infrared (940 nm): $I_e/I_e(20\text{mA}) = f(I_F)$; s. p.; $t_p = 100 \mu\text{s}$




Max. Permissible Forward Current

- true green: $I_{F,max} = f(T_S)$; $Rth_{js} = 260K / W$




Max. Permissible Forward Current

- hyper red: $I_{F,max} = f(T_S)$; $Rth_{js} = 310K / W$




Max. Permissible Forward Current

- infrared (940 nm): $I_{F,max} = f(T_S)$; $Rth_{js} = 380K / W$




Permissible Pulse Handling Capability

• true green: $I_F = f(t_p)$; $D = \text{parameter}$; $T_s = 25^\circ\text{C}$




Permissible Pulse Handling Capability

• hyper red: $I_F = f(t_p)$; $D = \text{parameter}$; $T_s = 25^\circ\text{C}$




Permissible Pulse Handling Capability

• infrared (940 nm): $I_F = f(t_p)$; $D = \text{parameter}$; $T_s = 25^\circ\text{C}$




Permissible Pulse Handling Capability

• true green: $I_F = f(t_p)$; $D = \text{parameter}$; $T_s = 85^\circ\text{C}$




Permissible Pulse Handling Capability

• hyper red: $I_F = f(t_p)$; $D = \text{parameter}$; $T_s = 85^\circ\text{C}$




Permissible Pulse Handling Capability

• infrared (940 nm): $I_F = f(t_p)$; $D = \text{parameter}$; $T_s = 85^\circ\text{C}$



Dimensional Drawing ¹⁰⁾




Further Information:


Approximate Weight: 3.0 mg

| Pin | Description |
|-----|------------------------------------|
| 1 | Cathode infrared emitter (940 nm) |
| 2 | Anode green/ red/ infrared emitter |
| 3 | Cathode green emitter (530 nm) |
| 4 | Cathode red emitter (655 nm) |
| 5 | Anode green/ red/ infrared emitter |
| 6 | NC |

Recommended Solder Pad ¹⁰⁾



Component Location on Pad




E062 3010.244 -03

For superior solder joint connectivity results we recommend soldering under standard nitrogen atmosphere.

Reflow Soldering Profile

Product complies to MSL Level 3 acc. to JEDEC J-STD-020E




| Profile Feature | Symbol | Pb-Free (SnAgCu) Assembly | | | Unit |
|---|--------|---------------------------|----------------|---------|------|
| | | Minimum | Recommendation | Maximum | |
| Ramp-up rate to preheat ^{*)} 25 °C to 150 °C | | | 2 | 3 | K/s |
| Time t_s T_{Smin} to T_{Smax} | t_s | 60 | 100 | 120 | s |
| Ramp-up rate to peak ^{*)} T_{Smax} to T_p | | | 2 | 3 | K/s |
| Liquidus temperature | T_L | | 217 | | °C |
| Time above liquidus temperature | t_L | | 80 | 100 | s |
| Peak temperature | T_p | | 245 | 260 | °C |
| Time within 5 °C of the specified peak temperature $T_p - 5$ K | t_p | 10 | 20 | 30 | s |
| Ramp-down rate* T_p to 100 °C | | | 3 | 6 | K/s |
| Time 25 °C to T_p | | | | 480 | s |

All temperatures refer to the center of the package, measured on the top of the component


* slope calculation DT/Dt : Dt max. 5 s; fulfillment for the whole T-range

Taping ¹⁰⁾



C67062-A0311-B1-01


Tape and Reel ¹¹⁾




Reel Dimensions

| A | W | N_{\min} | W_1 | $W_{2\max}$ | Pieces per PU |
|--------|----------------------|------------|--------------|-------------|---------------|
| 180 mm | $8 + 0.3 / - 0.1$ mm | 60 mm | $8.4 + 2$ mm | 14.4 mm | 3000 |

Barcode-Product-Label (BPL)



Dry Packing Process and Materials ¹⁰⁾



Notes

The evaluation of eye safety occurs according to the standard IEC 62471:2006 (photo biological safety of lamps and lamp systems). Within the risk grouping system of this IEC standard, the device specified in this data sheet fall into the class **exempt group (exposure time 10000 s)**. Under real circumstances (for exposure time, conditions of the eye pupils, observation distance), it is assumed that no endangerment to the eye exists from these devices. As a matter of principle, however, it should be mentioned that intense light sources have a high secondary exposure potential due to their blinding effect. When looking at bright light sources (e.g. headlights), temporary reduction in visual acuity and afterimages can occur, leading to irritation, annoyance, visual impairment, and even accidents, depending on the situation.

Subcomponents of this device contain, in addition to other substances, metal filled materials including silver. Metal filled materials can be affected by environments that contain traces of aggressive substances. Therefore, we recommend that customers minimize device exposure to aggressive substances during storage, production, and use. Devices that showed visible discoloration when tested using the described tests above did show no performance deviations within failure limits during the stated test duration. Respective failure limits are described in the IEC60810.

For further application related information please visit www.osram-os.com/appnotes

Disclaimer

Attention please!

The information describes the type of component and shall not be considered as assured characteristics. Terms of delivery and rights to change design reserved. Due to technical requirements components may contain dangerous substances.

For information on the types in question please contact our Sales Organization.

If printed or downloaded, please find the latest version on our website.

Packing

Please use the recycling operators known to you. We can also help you – get in touch with your nearest sales office. By agreement we will take packing material back, if it is sorted. You must bear the costs of transport. For packing material that is returned to us unsorted or which we are not obliged to accept, we shall have to invoice you for any costs incurred.

Product and functional safety devices/applications or medical devices/applications

Our components are not developed, constructed or tested for the application as safety relevant component or for the application in medical devices.

Our products are not qualified at module and system level for such application.

In case buyer – or customer supplied by buyer – considers using our components in product safety devices/ applications or medical devices/applications, buyer and/or customer has to inform our local sales partner immediately and we and buyer and /or customer will analyze and coordinate the customer-specific request between us and buyer and/or customer.

Glossary

- 1) **Radiant intensity:** Measured at a solid angle of $\Omega = 0.01$ sr
- 2) **Brightness:** The brightness values are measured with a tolerance of $\pm 11\%$.
- 3) **Reverse Operation:** This product is intended to be operated applying a forward current within the specified range. Applying any continuous reverse bias or forward bias below the voltage range of light emission shall be avoided because it may cause migration which can change the electro-optical characteristics or damage the LED.
- 4) **Wavelength:** The wavelengths are measured with a tolerance of ± 1 nm.
- 5) **Forward Voltage:** The forward voltages are measured with a tolerance of ± 0.1 V.
- 6) **Total radiant flux:** Measured with integrating sphere.
- 7) **Thermal resistance:** junction - soldering point, of the device only, mounted on an ideal heatsink (e.g. metal block)
- 8) **Typical Values:** Due to the special conditions of the manufacturing processes of semiconductor devices, the typical data or calculated correlations of technical parameters can only reflect statistical figures. These do not necessarily correspond to the actual parameters of each single product, which could differ from the typical data and calculated correlations or the typical characteristic line. If requested, e.g. because of technical improvements, these typ. data will be changed without any further notice.
- 9) **Testing temperature:** TA = 25°C (unless otherwise specified)
- 10) **Tolerance of Measure:** Unless otherwise noted in drawing, tolerances are specified with ± 0.1 and dimensions are specified in mm.
- 11) **Tape and Reel:** All dimensions and tolerances are specified acc. IEC 60286-3 and specified in mm.

Revision History

| Version | Date | Change |
|---------|------------|--|
| 1.0 | 2019-07-08 | Initial Version |
| 1.1 | 2019-09-27 | Characteristics Glossary |
| 1.2 | 2020-08-06 | New Layout Schematic Transportation Box Dimensions of Transportation Box |
| 1.3 | 2021-05-27 | Features |
| 1.4 | 2021-11-17 | Characteristics Electro - Optical Characteristics (Diagrams) |
| 1.5 | 2022-04-12 | Characteristics Derating (Diagrams) New Layout |



EU RoHS and China RoHS compliant product

此产品符合欧盟 RoHS 指令的要求；
按照中国的相关法规和标准，
不含有毒有害物质或元素。

Published by ams-OSRAM AG

Tobelbader Strasse 30, 8141 Premstaetten, Austria

Phone +43 3136 500-0

ams-osram.com

© All rights reserved

am 

OSRAM