

Slim Line Keypad G84-4700

USB version

Numeric Keypad



Key benefits

Cherry ML technology
with Gold Crosspoint contacts

21 keys, thereof four individually inscribable
function keys

Small dimensions

Ideal for right- and left-hand users

All keys programmable by software
„Cherry-Tools“

Combo Interface (USB · PS/2)

Approvals

WHQL (Windows Hardware Quality Lab)
"Designed for Windows 2000 and XP"

CE, GS/ÜG, VDE, cURus, FCC DoC Cl. B,
VCCI Cl. 2, BSMI, C-Tick, GOST-R

System requirements

USB connection

Windows 98, ME, 2000, XP
(for programming of keys by software)

Delivery volume

Keypad, printed instructions,
CDROM (software, manual)

Technische Daten

Interface

USB
PS/2 with adaptor (not included in delivery)

Current consumption

USB: max. 100 mA
PS/2 (with adaptor): approx. 50 mA

Number of keys

21 (4 keys inscribable)

Operating life of individual keys

> 50 million operations

Cable length

approx. 1,75 m

Weight

approx. 185 g (without packaging)
approx. 270 g (with packaging)

Dimensions

approx. 90 x 132 x 36 mm (Keypad)
approx. 140 x 185 x 45 mm (packaging)

Reliability

MCBF > 10⁹ operations
MTBF > 100,000 hours

Storage temperature

-25 °C to 65 °C

Operating temperature

0 °C to 50 °C

Packaging unit

72 keypads per master carton
576 keypads per palette

Guarantee period

2 years

Order description

Order no.	Colour	Interface
G84-4700LUCxx-0	light grey	USB
G84-4700PUCxx-2	black	USB

The xx in the order no. defines the country version.

BE	Belgium
CH	Switzerland
DE	Germany
DK	Denmark
ES	Spain
EU	US English/international with €
FR	France
GB	English (UK)
IT	Italy
NO	Norway
PO	Portugal
SF	Sweden / Finland
US	English (US)

Other versions upon request.

Cherry GmbH
Cherrystraße
D-91275 Auerbach/Opf.
Phone: +49 9643 18-0
Hotline: +49 9643 18-206
Fax: +49 9643 18-1545
Internet: www.cherrycorp.com

The manufacturer accepts no liability for errors or non-availability, and reserves the right to change specifications without prior notice. Technical data relate to product specifications only. Features may differ from those described. Only drawings combined with product specifications shall be deemed binding.