




UD12-6-6-SS

Ruland UD12-6-6-SS, 3/8" x 3/8" Double Universal Joint, Friction Bearing, Stainless Steel, 0.745" OD, 3.813" Length





Description

Ruland UD12-6-6-SS is a double cardan friction bearing universal joint with 0.3750" x 0.3750" bores, 0.745" OD, and 3.813" length. It is ideal for applications with wide distances between shafts and can accommodate all forms of misalignment. This plain bearing double universal joint is comprised of pins and blocks that are precision machined, selectively heat treated, and ground for high strength, accuracy, and wear resistance. The combination of these components with precision ground and hardened yoke ears allow for a longer lifespan, increased performance in demanding applications, and greater angular misalignment of up to 90° when compared to commodity style double universal joints. UD12-6-6-SS is made from high grade stainless steel for increased corrosion resistance. It can be combined with boot UBOOT12/19-NI-KIT to protect the joints from unwanted contaminants such as dust or water and self lubricate reducing maintenance time. This double cardan universal joint is manufactured in the USA by Belden Universal for strict control of processes.

Product Specifications

0.3750 in	Small Bore (B2)	0.3750 in
0.950 in	B2 Max Shaft Penetration	0.950 in
0.745 in	Bore Tolerance	+0.0010 in / -0.0000 in
3.813 in	Center Yoke Length (LC)	1.125 in
1.344 in	Hub Depth (LH)	0.950 in
790 in-lb	Rated Torque	158 in-lb
90°	Material Specification	Yokes: 303 Stainless Steel Pins and Blocks: 416 Stainless Steel
Belden Universal	Country of Origin	USA
0.335000	Recommended Lubricant	LUBRIPLATE No. 1200-2
UBOOT12/19-NI-KIT	UPC	634529288276
8483.60.4000	UNSPC	25173810
Performance ratings are for guidance only. The user must determine suitability for a particular application.		
•		
	0.950 in 0.745 in 3.813 in 1.344 in 790 in-lb 90° Belden Universal 0.335000 UBOOT12/19-NI-KIT 8483.60.4000 Performance ratings are for g	0.950 in B2 Max Shaft Penetration 0.745 in Bore Tolerance 3.813 in Center Yoke Length (LC) 1.344 in Hub Depth (LH) 790 in-lb Rated Torque 90° Material Specification Belden Universal Country of Origin 0.335000 Recommended Lubricant UBOOT12/19-NI-KIT UPC 8483.60.4000 UNSPC