

APPLICATOR PARTS LIST

TYPE  
LENGTHWISE RING  
AMPLINAR  
STUD RETAINING

AMP INCORPORATED  
HARRISBURG, PENNA.

THIS DRAWING IS A CONTROLLED DOCUMENT.

NO.	DESCRIPTION	REQ.	PART NO.	NO.	DESCRIPTION	REQ.	PART NO.
1	WIRE CRIMPER	1	456408-6	42	BENDING TOOL	1	458961-4
2	INS. CRIMPER			43			
3	ANVIL	1	2-473405-5	44			
4	ANVIL SPACER			45			
5	SHEAR BLADE	1	375307	46			
6	REAR SHEAR PLATE	1	385013-4	47			
7	SHEAR BLADE SPACER	2	370748	48			
8	FRONT BEND. PLATE	1	F-386017-5	49			
9	REAR ANVIL SPACER PLT.			50			
10	FRONT ANVIL SPACER PLT.	1	F-387158-6	51			
11	TOOL SPACER	1	470493-6	52			
12	SPACER	1	F-470493-4	53			
13	FRONT STRIP GUIDE	1	B10144-1	54			
14	REAR STRIP GUIDE	1	B10144-2	55			
15	RAM	1	471167	56			
16	TOOL HOLDER	1	376046	57	SCREW, DRIVE	3	21017-6
17	ADJ. CRIMP MOUNT			58	PLATE, IDENTIFICATION	1	452373-1
18	ADJ. BLOCK			59			
19	APPLICATOR MOUNT ASSY.	1	570656	60			
20	BASE PLATE			61			
21	BASE BLOCK			62			
22	STRIP GUIDE PLATE			63			
23	ANVIL HOLDER	1	370526	64			
24	AUX. ANVIL HOLDER	1	377515	65	TENSION ADJ PLATE	1	374997
25	STRIPPER	1	811654-2	MISCELLANEOUS			
26	STRIPPER MOUNT	2	386231	66	<del>AIR FEED ASSY</del>		
27	RETAINER PLATE	2	372251	67	<del>TOOL HOLDER</del>		
28	STRIPPER MOUNT BRACKET			68			
29	STRIPPER BUSHING			69	AIR FEED DELAY ASSY	1	809806-1
30	STOCK DRAG	1	375381	70	LUBRICATOR ASSY	1	46518A-2
31	STOCK DRAG HANDLE			71	TERMINAL LUBRICANT	1	22014-1
32	STOCK DRAG STUD	2	354045-1	72	AIR FEED ASSY 2"	1	690021
33	STOCK DRAG SPRING	2	1-23347-1	REV. REVISION RECORD			
34	STOCK DRAG ADJ. SCREW	2	372997	DATE	BY	ECN	
35	FEED FINGER HOLDER			A	ECN R-6296	6-85	HA/EE
36	FEED FINGER	1	375093	B	ECN R-6488	10-85	HA/EE
37	FEED FINGER TIP			C	EC-A-262690	8-6-90	HA/EE
38	FEED FINGER SPACER			D	0150-6407-95	9/95	LSC/EE
39	BASE CASTING	1	570238	E	0150-6525-95	11/95	LSC/EE
40	GUARD	1	457664-7	F	ECN 0150-9329-99	5-99	JTB
41				G	0150-9462-99	7-99	HA

CRIMPING DATA			TERMINALS
TO APPLY TERMINAL			505017
MAG			
WIRE SIZE	CRIMP HEIGHT		
20	.054		
18	.057		
16	.062		WITH LEG
			505072
CRIMP	SIZE	TYPE	FEED
WIRE	.110	F	
INSUL.			1.000
SLEEVED			
INSULATION RANGE	WIRE RANGE		
	20-16 MAG		

EXPLODED VIEW  
A-6000 A-6000-1

REMARKS:  
TOP TOOL MTG:  
ITEM 5, 12, 42, 11, 1

BOTTOM TOOL MTG:  
ITEM 6, 7, 8, 10, 3

REAR STRIP GUIDE  
ADJUSTMENT REQUIRED  
WHEN CHANGING FROM  
ONE PRODUCT TO THE  
OTHER

■ DENOTES WEARING PARTS  
RECOMMEND PURCHASE REPLACEMENT

THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP INC. IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION.

THIS APPLICATOR IS TO BE USED ON		DIST.
AMP-O-LECTRIC 1-471273-2		4
ALIGN. GA.	679597-1	
SERIAL NO.	DATE SHIPPED	DESIGNED
		3/29/95
CUSTOMER NAME AND ADDRESS		CHK'D
		4-9-95
APPLICATOR NUMBER	REV. G 566260-3	APP'D.
		1/8/98

THIS DRAWING IS UNCONTROLLED. ALL RIGHTS RESERVED. BY AMP INCORPORATED. © COPYRIGHT 1989