

8606 - Oil Pressure Switches Series



Series:

[Questions? Contact Littelfuse Support](#)

Feedback

Normally On, Off at: 2 - 6 psi (13.8 – 41.4 kPa).
.250" blade terminal. 1/8" -27 mounting stem. Self-grounding SPST Contacts open at rising pressure, close at falling pressure.
Heavy duty construction.
Weather-resistant. Plated steel case.
Molded moisture-repellent insulators.
Conservative burst pressure: 750 psi (5171.1 kPa).
Replaces AMC 1539889, 3142826, Chrysler 4169629, Delco 499581, 534598, 1359289, 1408319, 1508319, 668, 1598319, 1994214, 1998713, 3200422, 3818783, 5653196, 397, 462, D-2471, Ford D0RY-9278-A, International 280891-C91, 356079-C, 425491-R91, 31428266, Motorcraft Sw-334, SWG-334, SWE- 1030, Trucks: Chevrolet 85-89, Dodge 85-86, GMC 85-89, International 59-67, 78-80.

Connect with Littelfuse

Sign up to receive special offers and news

For more details about how we use your information, check our [Privacy Statement](#).

[Linked In](#) [Littelfuse](#) [Google Plus](#) [Facebook](#)
[Twitter](#) [Littelfuse](#) [YouTube](#) [Weibo](#) [RSS](#)

Mobile Site

About Littelfuse

- [About Littelfuse](#)
- [Conflict Free Statement](#)
- [History](#)
- [Investor Relations](#)
- [Legal](#)
- [Press Room](#)
- [Privacy Statement](#)
- [Supply Chain Transparency](#)
- [Website Feedback](#)

Explore Littelfuse

- [Capabilities Brochures](#)
- [Careers](#)
- [Check Distributor Stock](#)
- [Competitor Cross Reference](#)
- [Industries](#)
- [Order Samples](#)
- [Products](#)
- [Services](#)

Technical Resources

- [Application Designs](#)
- [Education](#)
- [FAQs](#)
- [iDesign™](#)
- [Littelfuse University](#)
- [Product Catalogs](#)
- [Quality Documents](#)
- [Technical Documents](#)