



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
01 ₂	REVISED	PATLAN 9-09-98	<i>[Signature]</i> 4/19/99
B	PER EC 0U20-0116-01-03	13NOV01	<i>C. Hoang</i> 13NOV01

COMPONENT	MATERIAL	FINISH
HOUSING COUPLING NUT SLIDE ASS'Y	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	ELECTRO-POLISHED
HOUSING	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	PASSIVATE PER QQ-P-35
CONTACT EXT.	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204
CENTER CONTACT	BRASS PER ASTM-B-16, HALF HARD	GOLD PLATE PER MIL-G-45204

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		DRAWN BY CD		DATE 6-30-82		AMP AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599	
FRAC. ± 1/64		CHECKED BY PCV		DATE 7-01-82			
DEC. ± .020		APP'D BY DRG		DATE 7-02-82			
These drawings and specifications are the property of AMP Interconnect Div. and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.		USE ASSY PROCEDURE		TITLE 7mm PRECISION TO "OSP" PLUG ADAPTER		NO. A.P. N/A	
		SIZE B		CODE IDENT NO. 26805		4581-2700-00	
		SCALE 4:1				REV 01 ₂	
						SHEET 1 OF 1	

NOTES:
 1. CAPTURED CENTER CONTACT
 2. SPECIFICATION;
 FREQ. RANGE: DC TO 18.0 GHz
 MAX VSWR 1.03 + .004f(GHz)

.XXX = in
 XX.X = mm (REF)