

## Teasing d<sup>M</sup> AntiMierobial

## **TECHNICAL DATA SHEET**

Part#: 530E-5-USL-CUSTOM

Cutters - Standoff Shear Small Frame - .XXX" Standoff - Narrow Jaw Reduces shock on delicate components and solder connections. Long ergonomic cushioned ESD safe handle.

The 530E-5-USL 6" narrow anti-shock shear cutter reduces shock on delicate components and solder connections. The "Stand-Off" keeps the cutting blade from cutting into the solder connections. The tip width is .090". It's recommended cutting capacity is 22 AWG (.25" soft wire). Recommended cutting capacity 22 AWG (.025") soft wire. It features a soft cushioned ergonomic Anti-Static grip (10<sup>10</sup> ohms/sq surface resistivity) with dual leaf springs.

\*\*\*\*

6" (150mm)

5.2

Precision LevelMaterial

Material Carbon
 Surface Resistivity 10<sup>10</sup> ohms/sq
 Shape Straight

• Type of Cut Shear • Cutting Capacity .025"

• Blade Angle

• Blade Length .095"

• Body Width 0.42" (10.5mm)


Body HeightOAL

• Weight (OZ)

• UPC N/A
• Schedule B 8203.20.60.30

• ECCN EAR99
• UNSPSC Code 27111511
• Country of Origin USA

• **Group** Small Frame





530E-5-USL Anti-Shock, Standoff Shear Cutter-Long Handle

A= .640° B= .100° C= .095°







