

Crimp contact - HC-D BUC 1,5 - 1772544


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Rolled socket contact (with BO crimp zone), for conductors with a cross section of 0.75 mm² - 1.5 mm². For contact insert order number 1580079



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	100 pc
GTIN	 4 017918 037215
Weight per Piece (excluding packing)	0.362 g
Custom tariff number	85369010
Country of origin	Germany

Technical data

General

Insertion/withdrawal cycles	≥ 20
Conductor cross section flexible min.	0.75 mm ²
Conductor cross section flexible max.	1.5 mm ²
Conductor cross section AWG min.	18
Conductor cross section AWG max.	16
Conductor cross section	0.75 mm ² ... 1.5 mm ²
Connection cross section AWG	18 ... 16
Assembly instructions	Only for contact inserts order number 1580079

Ambient conditions

Ambient temperature (operation)	-40 °C ... 125 °C
---------------------------------	-------------------

Material data

Crimp contact - HC-D BUC 1,5 - 1772544

Technical data

Material data

Contact material	Copper alloy
Contact surface material	Silver

Classifications

eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27140816
eCl@ss 5.0	27143424
eCl@ss 5.1	27143424
eCl@ss 6.0	27143424
eCl@ss 7.0	27440209
eCl@ss 8.0	27440204
eCl@ss 9.0	27440204

ETIM

ETIM 2.0	EC000796
ETIM 3.0	EC000796
ETIM 4.0	EC000796
ETIM 5.0	EC000796

UNSPSC

UNSPSC 6.01	30211923
UNSPSC 7.0901	39121522
UNSPSC 11	39121522
UNSPSC 12.01	39121522
UNSPSC 13.2	39121522

Approvals

Approvals

Approvals

EAC / EAC

Ex Approvals

Crimp contact - HC-D BUC 1,5 - 1772544

Approvals

Approvals submitted

Approval details

EAC

EAC

Drawings

Dimensional drawing

