

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT - BY -

ALL RIGHTS RESERVED.

LOC  
APDIST  
-

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
K3		REVISED PER ECO-11-005139	19MAR11	RK	HMR
K4		REVISED BY ECO-12-020337	22NOV2012	PP	WS
K5		REV. BY ECO 16-010419	14JULY2016	HC	WLS
L		REVISED PER ECN-23-214009	23MAY2023	WLS	JS

5,7±0,2

4,6

6,3±0,2

SEE DETAIL B

7,9

1,0

18,0

SECTION A-A

5,7

11,2±0,2


△ 1 RAW MATERIAL ACC. TO SPEC. IEC 60335-1 GWEPT 750°C, WITHOUT FLAME.

△ 2 PACKAGING QUANTITY ARE 1000 PARTS/BOX.

△ 3 CAVITY NUMBER IDENTIFICATION.

DETAIL B (SCALE 16:1)  
OPTIONAL CONSTRUCTION

OBSOLETE	NATURAL	MADE FROM 626064	1-0626064-3 △ 2
	NATURAL	PA 6.6 V-0 △ 1	1-0626064-2
	BLACK	PA 6.6	626064-5
OBSOLETE	RED	PA 6.6	626064-1
	NATURAL	PA 6.6	626064-0
FINISH		MATERIAL	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN E. LOPES 14MAR2006	 TE Connectivity		
DIMENSIONS: mm		CHK P. L. FARIA 14MAR2006			NAME
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD M. S. OLIVEIRA 14MAR2006			
0 PLC ±- 1 PLC ±0,15 2 PLC ±- 3 PLC ±- 4 PLC ±- ANGLES ±30' FINISH SEE TABLE		PRODUCT SPEC -			2 WAY .110 FASTIN-ON RECEP. HSG
MATERIAL SEE TABLE	FINISH SEE TABLE	APPLICATION SPEC -	WEIGHT -	SIZE A3	
		Customer Drawing	SCALE 3:1	CAGE CODE 00779	
			DRAWING NO C-626064	RESTRICTED TO -	
				SHEET 1	
				OF 1	
				REV L	

1470-19 (3/11)