



PCB Layout, Component side,
PCB thickness 1.6 mm

SPECIFICATION

| | |
|-----------------------|--------------|
| Mating Cycles | 500 |
| Filter type | C |
| Capacitance | 1000pf ± 20% |
| Working Voltage | 100v |
| Current Rating | 7.5A |
| Insulation Resistance | >1GΩ |

| FREQUENCY (MHz) | ATTENUATION (dB) |
|-----------------|------------------|
| 5 | 1dB |
| 10 | 3dB |
| 50 | 12dB |
| 100 | 20dB |
| 500 | 34dB |
| 1000 | 30dB |

| | | | | | | | | | | | | | |
|-------------|--|------------|--|-------|---------|--------------|--------------|------|--|---|---------------------------------------|-------------------------------|--|
| | | | | | Dat. | | Name | | <p>All Dim. in mm Orig. Size DIN A 4</p> | <p>D-Sub, female, straight, 9 Poles, solder pins, tin plated shell with spacer nuts and board-locks</p> | <p>Mo?Ms Lab/ Scale 1.5:1</p> | | |
| | | | | | Detail. | | 8 - JUL - 02 | | | | | CV | |
| | | | | | Insp. | | | | | | | | |
| | | | | | Stand. | | | | | | | | |
| 09641127236 | | M3 | | 33079 | | 29/08/05 | | JMDR | | <p>HARTING EURL F-95972 Paris</p> | | <p>TB 0964112723x</p> | |
| 09641127235 | | UNC 4-40 | | 31058 | | 8 - JUL - 02 | | CV | | | | | |
| Part number | | Nut thread | | Mod. | | Dat. | | Name | | Sub. | | <p>Blatt / Page 2 / 3</p> | |