



No. of pos.	A ±0.2	B ±0.1	C ±0.2	D ±0.1	Part-NO.
10	32.00	27.94	17.82	4x2.54=10.16	141A10019X
14	37.08	33.02	22.90	6x2.54=15.24	141A10029X
16	39.62	35.56	25.44	7x2.54=17.78	141A10039X
20	44.70	40.64	30.52	9x2.54=22.86	141A10049X
26	52.32	48.26	38.14	12x2.54=30.48	141A10059X
34	62.48	58.42	48.30	16x2.54=40.64	141A10069X
40	70.10	66.04	55.92	19x2.54=48.26	141A10079X
50	82.80	78.74	68.62	24x2.54=60.96	141A10089X
60	95.50	91.44	81.32	29x2.54=73.66	141A10099X
64	100.58	96.52	86.40	31x2.54=78.74	141A12289X

NOTES:

- INSULATORS: PBT UL 94 V-0, GREY
- CONTACTS: COPPER ALLOY
PLATING: GOLD over NICKEL
50 MATING CYCLES
- OPERATING TEMPERATURE RANGE: -40°C TO +105°C
- CURRENT CARRYING CAPACITY: 1 A
- DIELECTRIC WITHSTANDING VOLTAGE: 1000 VDC
- CONNECTOR IS PART MARKED: PART-NO. CONEC ABC

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY, WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND

rev.	description	date	name
a	Original		

tolerance		dim. in mm	
2014	date	name	
drawn	13.10.	Henneboel	
appd.	13.10.	Lehmenkühler	
norm	DIN 41651		
d-old			

scale:	2:1	
material:	SEE NOTES	
title:	HEADER 10-64pos. STRAIGHT SOLDER PINS 2.9mm	
dwg no:	14K1A033	DIN-A 3 sh:1/1
part no:	SEE TABLE	