




REVISIONS REV ECO DESCRIPTION DATE BY **APPR** RELEASE DRAWING 24AUG/19 PETER TOMMY








NOTES: UNLESS OTHERWISE SPECIFIED

 MATERIAL: HOUSING: THERMOPLASTIC SEAL: SILICONE RUBBER

- 2. MODIFICATIONS: REDUCED DIAMETER WIRE SEAL
- 3. SPECIFICATIONS:
 - 3.1 CURRENT RATING: 25 AMPS
 - 3.2 OPERATING TEMPERATURE: -55°C TO +125°C
 - 3.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
 - 3.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.
 - 3.5 MOISTURE RESISTANCE: IP67 (MATED CONDITION)
 - 3.6 MATING CYCLE DURABILITY: 100 CYCLES
 - 3.7 RoHS COMPLIANT
- 4. MATING PART: ATP06-6S* PLUG. (* = MODIFICATIONS AND COLORS)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.


6	CONTACT	SIZE AND RE	AR SEAL WIF	RE RANGE:

CONTACT	MIN. INSUL		TYPICAL
SIZE	O.D.		WIRE RANGE
12	2.46 mm (.097 in)	4.01 mm (.158 in)	12 - 14 AWG



PART NUMBER CHART			
COLOR PART NUMBER			
GREY	ATP04-6P-RD01		
BLACK	ATP04-6P-RD01BK		

STANDARD MOLDED COLOR IS GREY. ADDITIONAL COLOR (BLACK) IS AVAILABLE VIA SPECIAL ORDER.



NEXT ASS'Y

REFER TO PART NUMBER CHART FOR AVAILABLE CONNECTOR COLORS



SEE PART NUMBER CHART PART NUMBER QUANTITY MATERIALS LIST UNLESS OTHERWISE SPECIFIED SIGNATURES DATE Amphenol All dimensions are in metric(mm). 2) Tolerances are as follows:

1 PL DEC ±0.30 | Fractions ±1/64 |
2 PL DEC ±0.15 | Angles ±1° PETER.YANG 24AUG/19 ORION.LI 24/JUN/19 Sine Systems - www.amphenol-sine.com 3) Note reference = X 44724 Morley Drive Clinton Township, MI 48036 TOMMY.XIE 24AUG/19 MATERIAL SPECIFICATIONS CUSTOMER: RECEPTACLE, 6 PIN, REDUCED DIAMETER SEAL, ATP SERIES THIS DRAWING IS SUPPLIED FOR INFORMATION ONLY, DESIGN FEATURES, SPECIFICATIONS AND PERFORMANCE DAT SHOWN HEREON ARE THE PROPERTY OF PROCESS SPECIFICATIONS В ATP04-6P-RD01XX THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL MANUFACTURING VARIATIONS.

SCALE: NONE

ATP04-6P-RD01XX REV: A1 SH:

SHEET 1 OF 1

RECEPTACLE, 6 PIN, REDUCED DIAMETER SEAL, ATP SERIES

DWG NO:

ATP Series™ - Contact Size 12 Options

Machined Contacts, Sockets & Pins					
Part Number	Description	Size	AWG	Туре	
AT60-204-12141-10	Male Contact - Pin, Nickel-plated	12	10-12	Machined	
AT62-203-12141-10	Female Contact - Socket, Nickel-plated	12	10-12	Machined	
AT60-220-1231	Male Contact - Pin, Gold-plated	12	12-14	Machined	
AT62-210-1231	Female Contact - Socket, Gold-plated	12	12-14	Machined	
AT60-204-12141	Male Contact - Pin, Nickel-plated	12	12-14	Machined	
AT62-203-12141	Female Contact - Socket, Nickel-plated	12	12-14	Machined	

DiagnosticGrade™ Machined Contacts, Sockets & Pins • Smaller AWG for Diagnostic Applications • Gold-plated • Increased Mating Cycles • Cost-effective				
Part Number Description		Size	AWG	Туре
65-54749	Male Contact - DiagnosticGrade™, Pin, Gold-plated	12	20	Machined
AT62-210-1231-1820 Female Contact - DiagnosticGrade™, Socket, Gold-plated		12	20	Machined

Tooling - Machined Contacts				
Part	Part Number	Description		
	CA-5D12	Universal Hand Crimp Tool, Size 12/16/20 (Machined contacts only)		
55	CA-5E12	Pneumatic Crimp Tool, Size 12/16/20 (Machined contacts only)		
E.	M300-25A	Hand Crimp Tool used with Crimp Locator MFX-3966, Size 12, 10AWG (Machined contacts only)		
	MFX-3966	Contact Locator used with Hand Crimp Tool M300-25A, Size 12, 10AWG (Machined contacts only)		

Contact Removal Tools			
Part	Part Number	Description	
-	ATRT-100	Used for removal of contacts for A Series™ products	
	AT11-337-1205	Contact Removal Tool, Plastic, Size 12	
6	A114017	Sealing Plug, Size 12, White	

Stamped & Formed Contacts, Sockets & Pins					
Part Number	Description	Size	AWG	Type	
AT60-12-0244	Male Contact - Pin, Gold-plated	12	10-12	Stamped & Formed	
AT62-12-0244	Female Contact - Socket, Gold-plated	12	10-12	Stamped & Formed	
AT60-12-0222	Male Contact - Pin, Nickel-plated	12	10-12	Stamped & Formed	
AT62-12-0222	Female Contact - Socket, Nickel-plated	12	10-12	Stamped & Formed	
AT60-12-0144	Male Contact - Pin, Gold-plated	12	12-14	Stamped & Formed	
AT62-12-0144	Female Contact - Socket, Gold-plated	12	12-14	Stamped & Formed	
AT60-12-0166	Male Contact - Pin, Nickel-plated	12	12-14	Stamped & Formed	
AT62-12-0166	Female Contact - Socket, Nickel-plated	12	12-14	Stamped & Formed	

Tooling - Stamped & Formed Contacts			
Part	Part Number	Description	
	MFX-3973	Crimp Die - Size 12 (S&F contacts only)	
	MFX-3985	Crimp Die - Svize 12 (S&F contacts only) 10-12AWG -02XX Series	
	ATT-12-00	Hand Crimp Tool - Size 12, 12AWG (S&F contacts only)	
	ATT-12-01	Hand Crimp Tool - Size 12, 10AWG (S&F contacts only)	