

Selection Guide

Part No.	Dice	Lens Type	Iv (mcd) @ 10 mA		Viewing Angle
			Min.	Typ.	2θ1/2
L-1034ID	HIGH EFFICIENCY RED (GaAsP/GaP)	RED DIFFUSED	3	8	70°

Note:

1. θ1/2 is the angle from optical centerline where the luminous intensity is 1/2 the optical centerline value.

Electrical / Optical Characteristics at T_A=25°C


Symbol	Parameter	Device	Typ.	Max.	Units	Test Conditions
λ _{peak}	Peak Wavelength	High Efficiency Red	627		nm	I _F = 20mA
λ _D	Dominate Wavelength	High Efficiency Red	625		nm	I _F = 20mA
Δλ _{1/2}	Spectral Line Half-width	High Efficiency Red	45		nm	I _F = 20mA
C	Capacitance	High Efficiency Red	15		pF	V _F = 0V; f = 1MHz
V _F	Forward Voltage	High Efficiency Red	2	2.5	V	I _F = 20mA
I _R	Reverse Current	High Efficiency Red		10	μA	V _R = 5V

Absolute Maximum Ratings at T_A=25°C

Parameter	High Efficiency Red	Units
Power dissipation	105	mW
DC Forward Current	30	mA
Peak Forward Current [1]	160	mA
Reverse Voltage	5	V
Operating/Storage Temperature	-40°C To +85°C	
Lead Solder Temperature [2]	260°C For 5 Seconds	

Notes:

- 1/10 Duty Cycle, 0.1ms Pulse Width.
- 2mm below package base.



High Efficiency Red L-1034ID

