3 METERS LENGTH






Connector A 112234 BNC Jack Straight Bulkhead - Rear Mount Brass Nickel 50 Ohm RG-174 Continuity/Hi-Pot Connector B 122454 TNC Jack Right Angle Bulkhead - Rear Mount Brass Nickel + Heatshrink

Connector B

Assembly & Label Notes

Connector A

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.



Part #:	112234	Part #:	RG-174	Part #:	122454
Description:	BNC Clamp BHD JK RG188 500	Description:	RG-174 - PE 0.1	Description:	TNC R/A BHD JK RG174 RG316 LMR100
Type:	BNC	Dielectric:	PE		50O
Gender:	Jack	Shielding:	Braid	Type:	TNC
Body Type:	Straight	Diameter:	0.1	Gender:	Jack
Contact Type:	Crimp	Impedance:	50 Ohm	Body Type:	Right Angle
Polarity:	Standard	Sheathing:	None	Contact Type:	Solder
Impedance:	50 Ohm	Testing:	Continuity Hi-Pot	Polarity:	Standard
Mounting:	Bulkhead - Rear Mount	Length:	3 Meters	Impedance:	50 Ohm
Body Material:	Brass	'		Mounting:	Bulkhead - Rear Mount
Body Finish:	Nickel			Body Material:	Brass
IP Rating:	None			Body Finish:	Nickel
Contact Material:	Beryllium Copper			IP Rating:	None
Contact Finish:	Silver			Contact Material:	Phosphor Bronze
Max. Freq.:	4 GHz			Contact Finish:	Gold
Booting:	BNC Jack Straight BHD			Max. Freq.:	11 GHz
· · · · J	- · · · · · · · · · · · · · · · · · · ·			Booting:	TNC Jack Right Angle
				Clocking:	0°

Cable



CONTROLLED DOCUMENT - DO NOT COPY

THIS DRAWING MAY CONTAIN PATENTED OR PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.

BNC-ST-JK/TNC-RA-JK G174 3M

Part No:

Q-040480003003M

UNLESS SPECIFIED TOLERANCE:

0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH

IS LESS THAN 12 INCHES