


NOTES:

1. ALL PARTS ARE BULK PACKED.
2. CONTACTS ARE ASSEMBLED IN CONNECTOR WITH SOLDER CUPS FACING DIRECTLY OUTWARD
3. ALL DIMENSIONS ARE REFERENCE EXCEPT THOSE WITH A TOLERANCE

ASSEMBLY P/N	CONTACT QTY.		CABLE O.D. RANGE
	#16	#26	
W8A82-8SG-P-513	2	6	.13-.15 [3.3-3.8]
W8A82-8SG-P-516			.16-.18 [4.1-4.6]
W8A82-8SG-P-519			.19-.21 [4.8-5.3]
W8A82-8SG-P-522			.22-.25 [5.6-6.3]
W8A82-8SG-P-526			.25-.27 [6.4-6.9]
W8A82-8SG-P-528			.26-.285 [6.6-7.2]



CUSTOMER APPROVAL

THIS DOCUMENT CONTAINS CONFIDENTIAL INFORMATION PROPRIETARY TO CONXALL CORPORATION. ANY REPRODUCTION, DISCLOSURE, OR USE OF THIS DOCUMENT /INFORMATION IS EXPRESSLY PROHIBITED UNLESS AUTHORIZED IN WRITING BY CONXALL CORPORATION.

APPROVED BY: _____

DATE: _____

A	MA	07-20-20	RELEASED PER PDR 16014-10
	PNK	01-18-18	PDR16014
REV.	INIT.	DATE	DESCRIPTION
			ORIG. DRAWN BY: PNK DATE: 01-18-18
ALL INFORMATION ILLUSTRATED IS THE PROPERTY OF "CONXALL CORPORATION". UNAUTHORIZED DUPLICATION OR DISTRIBUTION OF THIS DOCUMENT IS PROHIBITED.			
ALL UNITS ARE IN FEET, INCHES, FRACTIONS OF INCHES AND DECIMALS.			
UNLESS OTHERWISE SPECIFIED TOLERANCES: 3 PLACE DECIMALS ±.010 ANGLES ±1° FRACTIONS ±1/16			
- CRITICAL CHARACTERISTIC FLAG PER SPEC. XXXX			
SCALE	SIZE	SHEET	<p>601 E. WILDWOOD VILLA PARK, IL 60181</p> <p>TITLE: CABLE-TO-CABLE ASSEMBLY 2-16 + 6-26 SOCKET CONTACTS, SOLDER INSTA-CLICK™ MINI-CON-X POWER/SIGNAL CUSTOMER: STANDARD PRODUCT</p>
NTS	B	1 OF 1	
FILE:	DIRECTORY:	PART NUMBER:	REV
W8A82-8SG-P-5XX	SLW	W8A82-8SG-P-5XX	A

DIMENSIONS IN BRACKETS [] ARE IN MILLIMETERS

RoHS COMPLIANT