

DIMENSIONS IN BRACKETS [] ARE IN MILLIMETERS


RoHS COMPLIANT

ASSEMBLY P/N	CONTA	ст qтү.	CABLE O.D. RANGE	
	#16	#26		
W8A80-8PG-P-513	-516 -519 -522 -526	6	.1315 [3.3-3.8]	
W8A80-8PG-P-516			.1618 [4.1-4.6]	
W8A80-8PG-P-519			.1921 [4.8-5.3]	
W8A80-8PG-P-522			.2225 [5.6-6.]	
W8A80-8PG-P-526			.25 .27 [6.4-6.9]	
W8A80-8PG-P-528			.26285 [6.6-7.2]	





1									
ſ	А	MA	07-15-20	RELEASED PER PDR 16014-10					
	~	PNK	01-18-18	PDR16014					
I	REV.	INIT.	DATE	DESCRIPTION					
	ALL INFORMATION ILLUSTRATED IS THE PROPERTY OF "CONXALL CORPORATION." UNAUTHORIZED DUPLICATION OR DISTRIBUTION OF THIS DOCUMENT IS PROHIBITED.			ORIG. DRAWN BY: DATE: PNK 01-18-18 Checked by:			conxall		
ŀ		ALL UNITS ARE IN FEET.					601 E. WILDWOOD VILLA PARK, IL 60181		
	INCHES, FRACTION OF INCHES AND DECIMALS, UNLESS OTHERWISE SPECIFIED TOLERANCES; 3 PLACE DECIMALS ±.010 ANGLES ±1° FRACTIONS ±1/16		APPROVED BY:			TITLE: CABLE-TO-CABLE ASSEMBLY 2-16 + 6-26 PIN CONTACTS, CRIMP			
			scale NTS	size B	sheet 1 OF 1	INSTA-CLICK™ MINI-CON-X POWER/SIG customer: STANDARD PRODUCT			
	\triangleright	FILE: DIRECTORY:			NUMBER: W8A80-8PG-P-5XX	REV A			



WIRING END