



**NOTE:**

1. ELECTRICAL CHARACTERISTICS
  - 1-1 RATING CURRENT: 2A AC/DC
  - 1-2 RATING VOLTAGE: 250V AC/DC
  - 1-3 WITHSTANDING VOLTAGE: 800V AC/1MINUTE
  - 1-4 OPERATING TEMPERATURE: -40°C~+105°C
  2. MATERIAL: REFER TO ORDERING CODE
  3. FINISH: BRIGHT TIN PLATING
  4. INSULATION O.D.: φ1.30MM MAX  
WIRE SIZE: AWG#24~26 (0.22~0.13mm<sup>2</sup>)
  5. USED WITH AFCI 10156614
  6. PRODUCT SPEC: GS-12-1594
  7. ORDERING CODE: 10156615-X 0 0 X LF
- MATERIAL:  BRASS  
 PHOSPHOR BRONZE
- PACKAGE:  REEL

SECTION: A-A  
SCALE: 1:1

SECTION: B-B  
SCALE: 1:1

SECTION: C-C  
SCALE: 1:1

RECOMMENDED PCB LAYOUT  
THICKNESS: 1.60MM

mat'l. code	surf'ce	tolerance	projection	product family
A	New release	ISO 1302	ISO 406	MINITEK
B	ECN no. 3610	ISO 1302	ISO 406	MINITEK
date		tolerances unless otherwise specified	110°	title
2020-2-19		angles: .XX±.20	mm	2.0PITCH BOARD-IN, Vertical , TERMINAL
2020-4-2		infeed: .XXX±.10	scale 2:1	dwg no
dr Jason Wang		0±x'		10156615
engr Jason Wang				sheet 1 of 1
chr -				size
qppd Tim Yao				A3
revision	B			type
sheet	1			Product Customer Drawing
index				