

In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



APPLICABLE STANDARD		STORAGE TEMPERATURE RANGE																																		
OPERATING TEMPERATURE RANGE	-35°C T0 +85°C (NOTES 1)	TEMPERATURE RANGE	-10°C T0 +60°C																																	
VOLTAGE	30V AC	APPLICABLE CONNECTOR	BM10*(0.8) -*DS-0.4V (**)																																	
CURRENT	0.3A																																			
SPECIFICATIONS																																				
ITEM	TEST METHOD	REQUIREMENTS	QT																																	
CONSTRUCTION			AT																																	
GENERAL EXAMINATION		CONFIRMED VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.																																	
MARKING	CONFIRMED VISUALLY.		X																																	
ELECTRIC CHARACTERISTICS			X																																	
CONTACT RESISTANCE	20mV AC OR LESS 1kHz, 1m A.	100mΩ MAX.	X																																	
INSULATION RESISTANCE	100V DC.	50MΩ MIN.	X																																	
VOLTAGE PROOF	100V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.	X																																	
MECHANICAL CHARACTERISTICS																																				
INSERTION AND WITHDRAWAL FORCES		MEASURED BY APPLICABLE CONNECTOR.	X																																	
		<table border="1"> <thead> <tr> <th>PN COUNTS</th> <th>INSERTION FORCE (N MAX)</th> <th>WITHDRAWAL FORCE (N MIN)</th> </tr> </thead> <tbody> <tr> <td>BM10*(0.8) -*DS-0.4V</td> <td></td> <td></td> </tr> <tr> <td>10</td> <td>15.4</td> <td>2.6</td> </tr> <tr> <td>16</td> <td>20.7</td> <td>3.6</td> </tr> <tr> <td>20</td> <td>24.3</td> <td>4.4</td> </tr> <tr> <td>24</td> <td>27.8</td> <td>5.1</td> </tr> <tr> <td>30</td> <td>33.1</td> <td>6.2</td> </tr> <tr> <td>34</td> <td>36.6</td> <td>6.9</td> </tr> <tr> <td>40</td> <td>41.9</td> <td>8.0</td> </tr> <tr> <td>50</td> <td>50.7</td> <td>9.8</td> </tr> <tr> <td>60</td> <td>59.5</td> <td>11.7</td> </tr> </tbody> </table>	PN COUNTS	INSERTION FORCE (N MAX)	WITHDRAWAL FORCE (N MIN)	BM10*(0.8) -*DS-0.4V			10	15.4	2.6	16	20.7	3.6	20	24.3	4.4	24	27.8	5.1	30	33.1	6.2	34	36.6	6.9	40	41.9	8.0	50	50.7	9.8	60	59.5	11.7	
PN COUNTS	INSERTION FORCE (N MAX)	WITHDRAWAL FORCE (N MIN)																																		
BM10*(0.8) -*DS-0.4V																																				
10	15.4	2.6																																		
16	20.7	3.6																																		
20	24.3	4.4																																		
24	27.8	5.1																																		
30	33.1	6.2																																		
34	36.6	6.9																																		
40	41.9	8.0																																		
50	50.7	9.8																																		
60	59.5	11.7																																		
MECHANICAL OPERATION	10TIMES INSERTIONS AND WITHDRAWAL.	① CONTACT RESISTANCE: 100mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X																																	
VIBRATION	FREQUENCY 10 TO 55 TO 10 Hz, APPROX 5min, SINGLE AMPLITUDE 0.75 mm, 100CYCLES, FOR 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X																																	
SHOCK	490 m/s <sup>2</sup> DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X																																	
ENVIRONMENTAL CHARACTERISTICS																																				
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55 → +85 °C TIME 30 → 30 min UNDER 5 CYCLES. (RELOCATION TIME TO CHAMBER: WITHIN 2 ~3 MIN)	① CONTACT RESISTANCE: 100mΩ MAX. ② INSULATION RESISTANCE: 50MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X																																	
DAMP HEAT (STEADY STATE)	EXPOSED AT 40 ± 2 °C, 90 TO 95 %, 96 h.	① CONTACT RESISTANCE: 100mΩ MAX. ② INSULATION RESISTANCE: 25MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X																																	
SULPHUR DIOXIDE	EXPOSED IN 25 PPM FOR 96h, 25°C, 75%. (REFER TO JIS C 60068)	① CONTACT RESISTANCE: 100mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X																																	
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED																																	
1	DIS-H-003833	NY. YAMASHIRO	TS. MIYAZAKI																																	
REMARKS		APPROVED	DATE																																	
NOTE1: INCLUDE THE TEMPERATURE RISING BY CURRENT		KH. IKEDA	09.04.15																																	
Unless otherwise specified, refer to JIS C 5402 and IEC 60512		CHECKED																																		
		KY. MIDORIKAWA	08.05.10																																	
		YH. MICHIDA	08.05.09																																	
		SH. HOSODA	08.01.12																																	
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC4-317902-01																																	
<b>HRS</b>																																				
SPECIFICATION SHEET		PART NO.	BM10B(0.8) -*DP-0.4V(51)																																	
HIROSE ELECTRIC CO., LTD.		CODE NO.	CL684-****-*51																																	
			1/1																																	