

Features/Benefits

- Designed for mirror control
- Wire harness and connector easy to customize
 Industrial
- 4-way adjustable directions

Typical Applications

- Automotive

Specifications

CONTACT RATING: 0.2 A @ 12 VDC OPERATING LIFE: 10,000 cycles

INSULATION RESISTANCE: 10 M Ω min. @ 500 VDC

DIELECTRIC STRENGTH: 500 V AC

OPERATING TEMPERATURE: -40°C to +90°C

OPERATING FORCE: L- OFF, R-OFF; 200 ±100 gf

> OFF-L, OFF-R; $400 \pm 200 \text{ gf}$ 4 Direction; $500 \pm 200 \text{ gf}$

Materials

KNOB: ABS COVER: ABS

TERMINAL: Brass, tin plated


NOTE: Specifications and materials listed above are for switches with standard options. For information on specific and custom switches, consult Customer Service Center.


How To Order

Part number list is shown below.

Part Number (Part Description)	Product Details	
CS-41001-E	4 directions switch with selector slide switch	

		<u>□40</u>
PART NUMBER	PACKAGING	R5
CS-41001-E	256 pieces	8 2
	<u>•</u>	3.5 1.8 3.5 5.25 P 17.5
	①— ⑤ Rv ⑥ Rh	— GND 36.0 ±0.10
	© <u>Lv</u> © <u>Tr</u>	38.7 0.10
		CHEMATIC







First Angle Projection

Dimensions are shown: mm Specifications and dimensions subject to change

