


APW-MW2-1210-010



FEATURES

- Low Cost
- 660 nm \pm 3nm
- 940 nm \pm 10 nm
- Optimal Peak Wavelength Binning
- Two Drive Lines

DESCRIPTION

The **APW-MW2-1210-010** is a two drive line dual emitter oximeter component. The 660nm and 940nm GaAIAs infrared emitters are mounted in a “glob top” low cost ceramic SMT 1210 package.

APPLICATIONS

- Oximeter Probes
- Finger Clamps
- Reusable Probes


> Absolute Maximum Ratings

Part No.	Continuous Forward Current [mA]	Peak Forward Current [mA]	Power Dissipation [mW]	Operating Temperature [C]	Storage Temperature [C]	Package
APW-MW2-1210-010	30	200	250	-40 to +80	-40 to +80	1210

> Electrical and Optical Characteristics


660nm Typical Characteristics (T=23°C unless specified)						
Parameter	Test Conditions	Symbol	Min	Typical	Max	Unit
Breakdown Voltage	$I_f = 10 \mu\text{A}$	V_{BD}	5	-	-	V
Radiant Flux	$I_f = 20 \text{mA}$	Φ_e	-	9.5	-	mW
Luminous Intensity	$I_f = 20 \text{mA}$	I_V	-	180	-	mcd
Forward Voltage	$I_f = 20 \text{mA}$	V_F	-	1.94	2.30	V
Peak Wavelength	$I_f = 20 \text{mA}$	λ_p	657	660	663	nm
Rise Time (50Ω load)	$I_f = 20 \text{mA}$	T_R	-	15	-	ns
Fall Time	$I_f = 20 \text{mA}$	T_F	-	15	-	ns
Spectral Halfwidth	$I_f = 20 \text{mA}$	$\Delta\lambda$	-	20	-	nm
940 nm Typical Characteristics (T=23°C unless specified)						
Parameter	Test Conditions	Symbol	Min	Typical	Max	Unit
Breakdown Voltage	$I_f = 10 \mu\text{A}$	V_{BD}	5	-	-	V
Radiant Flux	$I_f = 20 \text{mA}$	Φ_e	-	5	-	mW
Luminous Intensity	$I_f = 20 \text{mA}$	I_V	-	-	-	mcd
Forward Voltage	$I_f = 20 \text{mA}$	V_F	-	1.5	1.65	V
Peak Wavelength	$I_f = 20 \text{mA}$	λ_p	930	940	950	nm
Rise Time (50Ω load)	$I_f = 20 \text{mA}$	T_R	-	15	-	ns
Fall Time	$I_f = 20 \text{mA}$	T_F	-	15	-	ns
Spectral Halfwidth	$I_f = 20 \text{mA}$	$\Delta\lambda$	-	50	-	nm

> Suggested PCB Layout




> 1210 Package [AWW-MW2-1210-010]

PACKAGING DIMENSIONS,mm



>Soldering Conditions



LEGAL DISCLAIMER

All products, product specifications, and data are subject to change without notice to improve reliability, function, design, or otherwise. Advanced Photonix, its affiliates, agents, employees and all persons acting on its or their behalf (collectively, "Advanced Photonix"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product. Advanced Photonix makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Advanced Photonix disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability. Statements regarding the suitability of products for certain types of applications are based on Advanced Photonix's knowledge of typical requirements that are often placed on Advanced Photonix products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Advanced Photonix's terms and conditions of purchase, including but not limited to the warranty expressed therein. Except as expressly indicated in writing, Advanced Photonix products are not designed for use in life-saving, or life-sustaining applications, or for any other application in which the failure of the Advanced Photonix product could result in personal injury or death. Customers using or selling Advanced Photonix products not expressly indicated for use in such applications do so at their own risk. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Advanced Photonix. Product names and markings noted herein may be trademarks of their respective owners.

MATERIALS SAFETY

This product is free of conflict minerals and meets REACH compliance. Please see website for reports.