

## Housing - HC-HV 3-TMQ-48/M1PG16S - 1773543

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

Sleeve housing, with double locking latch, height 48 mm, with screw connection, 1x Pg16, lateral cable entry



### Key commercial data

|                                      |  |
|--------------------------------------|--|
| Packing unit                         | 1 pc   |
| GTIN                                 | <br>4 017918 037741 |
| Weight per Piece (excluding packing) | 219.92 GRM   |
| Custom tariff number                 | 85389099   |
| Country of origin                    | Germany  |

### Technical data

#### Dimensions

|                         |                  |
|-------------------------|------------------|
| Height                  | 48 mm            |
| Width                   | 43 mm            |
| Length                  | 73 mm            |
| Wrench size, union nut  | 22 mm            |
| External cable diameter | 7.5 mm ... 15 mm |

#### Ambient conditions

|                                      |                   |
|--------------------------------------|-------------------|
| Degree of protection of housing (IP) | IP65              |
| Ambient temperature (operation)      | -40 °C ... 125 °C |

#### General

|              |                            |
|--------------|----------------------------|
| Note         | For contact inserts HV-HV3 |
| Design       | HV3                        |
| Housing type | Sleeve housings            |

# Housing - HC-HV 3-TMQ-48/M1PG16S - 1773543

## Technical data

### General

|                              |                           |
|------------------------------|---------------------------|
| Locking type                 | With double locking latch |
| No. of cable exits           | 1                         |
| Cable exit                   | Lateral                   |
| Screw connection             | With                      |
| Type of the screw connection | 1x Pg16                   |
| Housing material             | Aluminum die-cast         |
| Housing surface material     | Powder-coated, gray       |
| Cable gland material         | Nickel-plated brass       |
| Cable seal material          | NBR                       |
| Material lock                | High-grade steel          |
| Material grip body interlock | PA-GF                     |

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27140816 |
| eCl@ss 4.1 | 27140816 |
| eCl@ss 5.0 | 27143424 |
| eCl@ss 5.1 | 27143424 |
| eCl@ss 6.0 | 27143424 |
| eCl@ss 7.0 | 27440209 |
| eCl@ss 8.0 | 27440209 |

### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000437 |
| ETIM 3.0 | EC000437 |
| ETIM 4.0 | EC000437 |
| ETIM 5.0 | EC000437 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 31261502 |
| UNSPSC 7.0901 | 31261502 |
| UNSPSC 11     | 31261502 |
| UNSPSC 12.01  | 31261502 |
| UNSPSC 13.2   | 31261502 |

## Approvals

### Approvals

# Housing - HC-HV 3-TMQ-48/M1PG16S - 1773543

## Approvals

---

Approvals

GOST

---

Ex Approvals

---

Approvals submitted

## Approval details



## Drawings

Dimensioned drawing

