CONFIDENTIAL & PROPRIETARY INFORMATION

This document contains Confidential and Proprietary Information of Alliance LLC, and all design, manufacturing, reproduction, use, and sale rights of such information are expressly reserved

ALL DIMENSIONS ARE IN MM (INCH)



NOTES:

1. MAGNET PROPERTIES PER N-35SH:

Br: 11,800-12,200 G Hc: 10,800-11,500 Oe Hci: ≥20,000 Oe T max: 150 C

- 2. SUPPLIED MAGNETIZED THROUGH THE THICKNESS
- 3. PARTS ARE NICKEL PLATED FOR 15 HRS SALT SPRAY MIN.

1		
4		
ı		
-	REACH COMPLIANT	

REV	DESCRIPTION	DATE	BY

TOLERANCES (UNLESS OTHERWISE NOTED)				
$ \begin{array}{ll} \text{DECIMAL} & \text{METRIC} \\ \text{X.XX} = \pm .01 & \text{X.X} = \pm .25 \\ \text{X.XXX} = \pm .005 & \text{X.XX} = \pm .13 \\ \end{array} $				
ANGLES ± .5°				
DO NOT SCALE DRAWING				

Alliance LLC 1450 CLARK DRIVE, VALPARAISO, INDIANA 46385						
DESCRIPTION: 4 mm x 4 mm DISC MAGNET						
SENSOR MAGNI	P/N: ALC4040					
GRADE: N-35SH	Drwg by: BT	REV LEVEL: A				
COATING: Nickel	Appr by: DV	Approval: 06-15-2017				