



SCALANCE X accessory; plug-in transceiver SFP991-1; 1x 100 Mbit/s LC port, optical; multimode optical up to max. 5 km 1 pack = 10 units.

| interfaces | |
|---|---|
| number of electrical/optical connections / for network components or terminal equipment / maximum | 1 |
| number of optical interfaces / for network components or terminal equipment / maximum | 1 |
| number of 100 Mbit/s LC ports | 1 |
| design of the optical interface / for network components or terminal equipment | LC |
| wavelength / of the optical interface | 1300 nm; Multi-mode |
| connectable optical power relative to 1 mW | |
| <ul style="list-style-type: none"> of the transmitter output / minimum of the transmitter output / maximum of the receiver input / maximum | -24 dB -14 dB -12 dB |
| optical sensitivity relating to 1 mW / of the receiver input / minimum | -31 dB |
| attenuation factor / of the FOC transmission link / minimum necessary | 0 dB |
| range / at the optical interface / depending on the optical fiber used | 0 ... 5 km |
| ambient conditions | |
| ambient temperature | |
| <ul style="list-style-type: none"> during operation during storage during transport note | -40 ... +85 °C -40 ... +85 °C -40 ... +85 °C A maximum operating temperature of +85 °C is permissible for a duration of 16 hours |
| relative humidity / at 25 °C / without condensation / during operation / maximum | 95 % |
| protection class IP | IP20 |
| design, dimensions and weights | |
| design | SFP Module |
| width | 14 mm |
| height | 9 mm |
| depth | 57 mm |
| net weight | 0.01 kg |
| fastening method | latched |
| standards, specifications, approvals | |
| standard | |
| <ul style="list-style-type: none"> for FM for hazardous zone for safety / from CSA and UL | FM3611: Class 1, Division 2, Group A, B, C, D / T4, Class 1, Zone 2, Group IIC, T4 EN 60079-0: 2006, EN60079-15: 2005, II 3 G Ex nA II T4, KEMA 07 ATEX 0145 X UL 60950-1, CSA C22.2 No. 60950-1-03 |

| | |
|--|--|
| <ul style="list-style-type: none"> • for emitted interference • for interference immunity | EN 61000-6-4:2007 (Class A) EN 61000-6-2:2005 |
| certificate of suitability <ul style="list-style-type: none"> • CE marking • C-Tick • KC approval | EN 61000-6-2:2005, EN 61000-6-4:2007 Yes Yes No |
| Marine classification association <ul style="list-style-type: none"> • French marine classification society (BV) | Yes |
| MTBF | 490 a |

further information / internet links

| | |
|--|---|
| internet link <ul style="list-style-type: none"> • to web page: selection aid TIA Selection Tool • to website: Industrial communication • to website: Industry Mall • to website: Information and Download Center • to website: Image database • to website: CAx-Download-Manager • to website: Industry Online Support | http://www.siemens.com/tia-selection-tool http://www.siemens.com/simatic-net https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com |
|--|---|

last modified:

5/24/2022 