



THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN AMP PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM AMP INCORPORATED, HARRISBURG, PA.

- $\triangle 1$ EYELETS MUST BE SEATED ON HANDLE AND TIP AS SHOWN. TIP SIDE PLAY NOT PERMISSIBLE.
- $\triangle 2$ SLOTTED SPRING PIN MUST BE SEATED .05 BELOW EACH END OF HANDLE.
- $\triangle 3$ MARKING TO BE CENTERED AND PERMANENTLY MARKED IN AREAS AS SHOWN. (COLOR OPTIONAL).
- 4. TOOL IS SPRING LOADED CLOSED, MUST OPEN AND CLOSE FREELY.
- $\triangle 5$.010 MAX GAP MEASURED FROM FRONT OF TIP, WITHIN .032 LENGTH.
- $\triangle 6$ MEASURED WITH $\phi .154$ PIN INSERTED INTO .63 TIP LENGTH.

2	A	21920-7	*PIN, DOWEL	6
2	A	126217-1	SPRING	5
1	B	445146-1	HANDLE, LEFT SIDE	4
1	B	445145-1	HANDLE, RIGHT SIDE	3
4	B	1-26024-4	EYELET	2
2	B	445144-1	EXTRACTION TIP, HALF	1

-1	DWG SIZE	PART NO	DESCRIPTION	ITEM NO
REVISION OF EACH ASSY NO (WHEN BLANK, USE DWG REVISION)				
PARTS LIST				
QTY REQD PER ASSY		MATERIAL	HEAT TREAT	FINISH
DIMENSIONS IN INCHES. TOLERANCES UNLESS OTHERWISE SPECIFIED:				
2 PLC DEC $\pm .01$				
3 PLC DEC $\pm .005$				
4 PLC DEC $\pm .$				
ANGLES $\pm .$				
SURF TEXTURE: \checkmark				
REMOVE BURRS, BREAK SHARP EDGES .015R MAX				
SCALE: 2:1		DWG NO: C	445147	SHEET: 1 of 1
		REV NO:		REV: C

PROD	5069
CODE	
LOC	DF
DIST	UO

P	F	LTR	REVISION RECORD	APP	DATE	P	F	LTR	REVISION RECORD	APP	DATE