

**Data sheet | Item number: 869-316**

2-conductor terminal block; without push-buttons; with snap-in mounting foot; 1-pole; for plate thickness 0.6 - 1.2 mm; Fixing hole 3.5 mm Ø; 2.5 mm<sup>2</sup>; CAGE CLAMP®; 2,50 mm<sup>2</sup>; orange

[www.wago.com/869-316](http://www.wago.com/869-316)



Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



## Data Notes

Safety information

Max. insulation diameter: 4.4 mm

## Electrical data

### Ratings per IEC/EN

|                               |   |
|-------------------------------|---|
| Nominal voltage (III/3)       | 500 V   |
| Rated impulse voltage (III/3) | 6 kV  |
| Rated current                 | 24 A  |
| Legend (ratings)              | (III / 3) $\hat{=}$ Overvoltage category III / Pollution degree 3 |

## Connection data

|                            |   |
|----------------------------|---|
| Connection points          | 2 |
| Total number of potentials | 1 |
| Number of levels           | 1 |

## Connection 1

|   |  |
|---|--|
| Connection technology                           | CAGE CLAMP <sup>®</sup>                      |
| Actuation type                                  | Operating tool                               |
| Connectable conductor materials                 | Copper                                       |
| Solid conductor                                 | 0.08 ... 2.5 mm <sup>2</sup> / 28 ... 12 AWG |
| Fine-stranded conductor                         | 0.08 ... 4 mm <sup>2</sup> / 28 ... 12 AWG   |
| Fine-stranded conductor; with insulated ferrule | 0.08 ... 1.5 mm <sup>2</sup> / 28 ... 14 AWG |
| Strip length                                    | 6 ... 7 mm / 0.24 ... 0.28 inches            |
| Wiring direction                                | Front-entry wiring                           |

## Physical data

|                         |                        |
|-------------------------|------------------------|
| Width                   | 5 mm / 0.197 inches    |
| Height from the surface | 27.6 mm / 1.087 inches |
| Depth                   | 33.4 mm / 1.315 inches |

## Mechanical Data

|        |                 |
|--------|-----------------|
| Design | horizontal type |
|--------|-----------------|

Subject to changes. Please also observe the further product documentation!



|               |              |
|---------------|--------------|
| Mounting type | Snap-in foot |
| Marking level | Side marking |

## Material Data

Note (material data)

Information on material specifications can be found here

|                             |                  |
|-----------------------------|------------------|
| Color                       | orange           |
| Material group              | I                |
| Insulation material         | Polyamide (PA66) |
| Flammability class per UL94 | V0               |
| Fire load                   | 0.073 MJ         |
| Halogen-free                | Yes              |
| Weight                      | 4 g              |

## Commercial data

|                       |               |
|-----------------------|---------------|
| eCl@ss 10.0           | 27-14-11-06   |
| eCl@ss 9.0            | 27-14-11-06   |
| ETIM 8.0              | EC001284      |
| ETIM 7.0              | EC001284      |
| PU (SPU)              | 100 pcs       |
| Packaging type        | box           |
| Country of origin     | DE            |
| GTIN                  | 4044918480062 |
| Customs tariff number | 85369010000   |

## Environmental Product Compliance

|                        |                         |
|------------------------|-------------------------|
| RoHS Compliance Status | Compliant, No Exemption |
|------------------------|-------------------------|

## Approvals / Certificates

### General approvals

| Logo | Approval                        | Additional Approval Text | Certificate name  |
|------|---------------------------------|--------------------------|-------------------|
|      | CCA<br>DEKRA Certification B.V. | EN 60947                 | 2143311.02        |
|      | CCA<br>DEKRA Certification B.V. | EN 60947                 | NTR NL<br>6827/A1 |
|      | UL                              | UL 1059                  | E45172            |

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
 Hansastr. 27  
 32423 Minden  
 Phone: +49571 887-0 | Fax: +49571 887-169  
 Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
 We are always happy to take your call at +49 (571) 887-44222.



UL International Germany GmbH

## Declarations of conformity and manufacturer's declarations

| Logo | Approval  | Additional Approval Text | Certificate name |
|------|---|--------------------------|------------------|
|      | <b>EU-Declaration of Conformity</b><br>WAGO GmbH & Co. KG | -                        | -                |
|      | <b>UK-Declaration of Conformity</b><br>WAGO GmbH & Co. KG | -                        | -                |

## Approvals for marine applications

| Logo | Approval  | Additional Approval Text | Certificate name         |
|------|---|--------------------------|--------------------------|
|      | <b>ABS</b><br>American Bureau of Shipping               | EN 60947                 | 20-<br>HG1941090-<br>PDA |
|      | <b>DNV GL</b><br>Det Norske Veritas, Germanischer Lloyd | -                        | TAE00001V2               |

## Counterpart

Item no.869-326

2-conductor terminal block; without push-buttons; without snap-in mounting foot; 1-pole; 2.5 mm<sup>2</sup>; CAGE CLAMP®; 2,50 mm<sup>2</sup>; orange[www.wago.com/869-326](http://www.wago.com/869-326)

## Required accessories

## End plate

| End plate   |  |
|---|--|
| <b>Item no.: 869-378</b><br>End plate; for terminal blocks with snap-in mounting foot; 2.5 mm thick; blue         | <a href="http://www.wago.com/869-378">www.wago.com/869-378</a> |
| <b>Item no.: 869-375</b><br>End plate; for terminal blocks with snap-in mounting foot; 2.5 mm thick; gray         | <a href="http://www.wago.com/869-375">www.wago.com/869-375</a> |
| <b>Item no.: 869-379</b><br>End plate; for terminal blocks with snap-in mounting foot; 2.5 mm thick; green-yellow | <a href="http://www.wago.com/869-379">www.wago.com/869-379</a> |
| <b>Item no.: 869-377</b><br>End plate; for terminal blocks with snap-in mounting foot; 2.5 mm thick; light gray   | <a href="http://www.wago.com/869-377">www.wago.com/869-377</a> |

## Optional accessories

## Jumpers

| Jumper |
|--------|
|--------|

Subject to changes. Please also observe the further product documentation!

WAGO GmbH &amp; Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.



|   |  |
|---|--|
| <b>Item no.: 870-402</b><br>Jumper; 2-way; insulated; light gray        | <a href="http://www.wago.com/870-402">www.wago.com/870-402</a>                 |
| <b>Item no.: 870-404</b><br>Jumper; 4-way; insulated; light gray        | <a href="http://www.wago.com/870-404">www.wago.com/870-404</a>                 |
| <b>Item no.: 870-405</b><br>Jumper; 5-way; insulated; light gray        | <a href="http://www.wago.com/870-405">www.wago.com/870-405</a>                 |
| <b>Item no.: 870-407</b><br>Jumper; 7-way; insulated; light gray        | <a href="http://www.wago.com/870-407">www.wago.com/870-407</a>                 |
| <b>Item no.: 870-408</b><br>Jumper; 8-way; insulated; light gray        | <a href="http://www.wago.com/870-408">www.wago.com/870-408</a>                 |
| <b>Item no.: 870-403</b><br>Jumper; 3-way; insulated; light gray        | <a href="http://www.wago.com/870-403">www.wago.com/870-403</a>                 |
| <b>Item no.: 870-409</b><br>Jumper; 9-way; insulated; light gray        | <a href="http://www.wago.com/870-409">www.wago.com/870-409</a>                 |
| <b>Item no.: 870-406</b><br>Jumper; 6-way; insulated; light gray        | <a href="http://www.wago.com/870-406">www.wago.com/870-406</a>                 |
| <b>Item no.: 870-433</b><br>Jumper; from 1 to 3; insulated; light gray  | <a href="http://www.wago.com/870-433">www.wago.com/870-433</a>                 |
| <b>Item no.: 870-435</b><br>Jumper; from 1 to 5; insulated; light gray  | <a href="http://www.wago.com/870-435">www.wago.com/870-435</a>                 |
| <b>Item no.: 870-410</b><br>Jumper; 10-way; insulated; light gray       | <a href="http://www.wago.com/870-410">www.wago.com/870-410</a>                 |
| <b>Item no.: 870-434</b><br>Jumper; from 1 to 4; insulated; light gray  | <a href="http://www.wago.com/870-434">www.wago.com/870-434</a>                 |
| <b>Item no.: 870-440</b><br>Jumper; from 1 to 10; insulated; light gray | <a href="http://www.wago.com/870-440">www.wago.com/870-440</a>                 |
| <b>Item no.: 870-406/020-000</b><br>Delta jumper; insulated; light gray | <a href="http://www.wago.com/870-406/020-000">www.wago.com/870-406/020-000</a> |

## Mounting

### Mounting accessories

|   |  |
|---|--|
| <b>Item no.: 209-120</b><br>Mounting foot; can be snapped on terminal blocks with snap-in mounting foot; for mounting on relay-modules; 6.4 mm wide; gray | <a href="http://www.wago.com/209-120">www.wago.com/209-120</a> |
|---|--|

## Protective warning marker

### Cover

|   |  |
|---|--|
| <b>Item no.: 280-405</b><br>Protective warning marker; for 5 terminal blocks; with high-voltage symbol, black; yellow | <a href="http://www.wago.com/280-405">www.wago.com/280-405</a> |
|---|--|

## Carrier rail

Subject to changes. Please also observe the further product documentation!



| Mounting accessories              |  |  |
|-----------------------------------|--|--|
| <b>Item no.: 210-154</b>          | Aluminum carrier rail; 1000 mm long; 18 mm wide; 7 mm high; silver-colored   | <a href="http://www.wago.com/210-154">www.wago.com/210-154</a>                   |
| Testing and measuring             |  |  |
| Testing accessories               |  |  |
| <b>Item no.: 870-425</b>          | Tap-off module; with anti-rotation protection; modular; suitable for 870 Series terminal blocks with jumper slots in the current bar; gray | <a href="http://www.wago.com/870-425">www.wago.com/870-425</a>                   |
| <b>Item no.: 870-426</b>          | Tap-off module; modular; suitable for 870 Series terminal blocks with jumper slots in the current bar; gray                                | <a href="http://www.wago.com/870-426">www.wago.com/870-426</a>                   |
| <b>Item no.: 870-427</b>          | Spacer module; modular; bridging commoned terminal blocks; gray  | <a href="http://www.wago.com/870-427">www.wago.com/870-427</a>                   |
| Insulation stop                   |  |  |
| Insulation stop                   |  |  |
| <b>Item no.: 280-472</b>          | Insulation stop; 0.75 - 1 mm <sup>2</sup> ; 5 pieces/strip; black  | <a href="http://www.wago.com/280-472">www.wago.com/280-472</a>                   |
| <b>Item no.: 280-470</b>          | Insulation stop; 0.08 - 0.2 mm <sup>2</sup> "s" (0.14 mm <sup>2</sup> "f-st"); 5 pieces/strip; white                                       | <a href="http://www.wago.com/280-470">www.wago.com/280-470</a>                   |
| <b>Item no.: 280-471</b>          | Insulation stop; 0.25 - 0.5 mm <sup>2</sup> ; 5 pieces/strip; light gray   | <a href="http://www.wago.com/280-471">www.wago.com/280-471</a>                   |
| Marking accessories               |  |  |
| Marking strip                     |  |  |
| <b>Item no.: 709-196</b>          | Marking strips; for laser printer; translucent   | <a href="http://www.wago.com/709-196">www.wago.com/709-196</a>                   |
| <b>Item no.: 709-178</b>          | Marking strips; on reel; 7.5 mm wide; not stretchable; plain; snap-on type; white  | <a href="http://www.wago.com/709-178">www.wago.com/709-178</a>                   |
| <b>Item no.: 709-177</b>          | Marking strips; on reel; 7.5 mm wide; not stretchable; plain; snap-on type; translucent  | <a href="http://www.wago.com/709-177">www.wago.com/709-177</a>                   |
| Marker                            |  |  |
| <b>Item no.: 2009-115/000-002</b> | WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; yellow                                    | <a href="http://www.wago.com/2009-115/000-002">www.wago.com/2009-115/000-002</a> |
| <b>Item no.: 2009-115/000-007</b> | WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; gray                                      | <a href="http://www.wago.com/2009-115/000-007">www.wago.com/2009-115/000-007</a> |
| <b>Item no.: 2009-115/000-017</b> | WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; light green                               | <a href="http://www.wago.com/2009-115/000-017">www.wago.com/2009-115/000-017</a> |

Subject to changes. Please also observe the further product documentation!



---

**Item no.: 2009-115/000-023** [www.wago.com/2009-115/000-023](http://www.wago.com/2009-115/000-023)  
WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; green

---

**Item no.: 2009-115/000-024** [www.wago.com/2009-115/000-024](http://www.wago.com/2009-115/000-024)  
WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; violet

---

**Item no.: 2009-145/000-006** [www.wago.com/2009-145/000-006](http://www.wago.com/2009-145/000-006)  
Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; blue

---

**Item no.: 2009-145** [www.wago.com/2009-145](http://www.wago.com/2009-145)  
Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; white

---

**Item no.: 2009-145/000-002** [www.wago.com/2009-145/000-002](http://www.wago.com/2009-145/000-002)  
Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; yellow

---

**Item no.: 2009-145/000-007** [www.wago.com/2009-145/000-007](http://www.wago.com/2009-145/000-007)  
Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; gray

---

**Item no.: 2009-145/000-005** [www.wago.com/2009-145/000-005](http://www.wago.com/2009-145/000-005)  
Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; red

---

**Item no.: 2009-145/000-012** [www.wago.com/2009-145/000-012](http://www.wago.com/2009-145/000-012)  
Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; orange

---

**Item no.: 2009-145/000-023** [www.wago.com/2009-145/000-023](http://www.wago.com/2009-145/000-023)  
Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; green

---

**Item no.: 2009-145/000-024** [www.wago.com/2009-145/000-024](http://www.wago.com/2009-145/000-024)  
Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; violet

---

**Item no.: 2009-115** [www.wago.com/2009-115](http://www.wago.com/2009-115)  
WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; white

---

**Item no.: 248-501/000-006** [www.wago.com/248-501/000-006](http://www.wago.com/248-501/000-006)  
Mini-WSB marking card; as card; not stretchable; plain; snap-on type; blue

---

**Item no.: 248-501/000-007** [www.wago.com/248-501/000-007](http://www.wago.com/248-501/000-007)  
Mini-WSB marking card; as card; not stretchable; plain; snap-on type; gray

---

**Item no.: 248-501/000-002** [www.wago.com/248-501/000-002](http://www.wago.com/248-501/000-002)  
Mini-WSB marking card; as card; not stretchable; plain; snap-on type; yellow

---

Subject to changes. Please also observe the further product documentation!

---

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



---

|  |  |
|--|--|
| <b>Item no.: 248-501/000-012</b><br>Mini-WSB marking card; as card; not stretchable; plain; snap-on type; orange | <a href="http://www.wago.com/248-501/000-012">www.wago.com/248-501/000-012</a> |
|--|--|

---

|   |  |
|---|--|
| <b>Item no.: 248-501</b><br>Mini-WSB marking card; as card; not stretchable; plain; snap-on type; white | <a href="http://www.wago.com/248-501">www.wago.com/248-501</a> |
|---|--|

---

|   |  |
|---|--|
| <b>Item no.: 248-501/000-017</b><br>Mini-WSB marking card; as card; not stretchable; plain; snap-on type; light green | <a href="http://www.wago.com/248-501/000-017">www.wago.com/248-501/000-017</a> |
|---|--|

---

|   |  |
|---|--|
| <b>Item no.: 248-501/000-005</b><br>Mini-WSB marking card; as card; not stretchable; plain; snap-on type; red | <a href="http://www.wago.com/248-501/000-005">www.wago.com/248-501/000-005</a> |
|---|--|

---

|  |  |
|--|--|
| <b>Item no.: 248-501/000-024</b><br>Mini-WSB marking card; as card; not stretchable; plain; snap-on type; violet | <a href="http://www.wago.com/248-501/000-024">www.wago.com/248-501/000-024</a> |
|--|--|

---

|   |  |
|---|--|
| <b>Item no.: 248-501/000-023</b><br>Mini-WSB marking card; as card; not stretchable; plain; snap-on type; green | <a href="http://www.wago.com/248-501/000-023">www.wago.com/248-501/000-023</a> |
|---|--|

---

|   |  |
|---|--|
| <b>Item no.: 793-5501/000-007</b><br>WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; gray | <a href="http://www.wago.com/793-5501/000-007">www.wago.com/793-5501/000-007</a> |
|---|--|

---

|   |  |
|---|--|
| <b>Item no.: 793-5501/000-012</b><br>WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; orange | <a href="http://www.wago.com/793-5501/000-012">www.wago.com/793-5501/000-012</a> |
|---|--|

---

|  |  |
|--|--|
| <b>Item no.: 793-5501/000-017</b><br>WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; light green | <a href="http://www.wago.com/793-5501/000-017">www.wago.com/793-5501/000-017</a> |
|--|--|

---

|  |  |
|--|--|
| <b>Item no.: 793-5501/000-023</b><br>WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; green | <a href="http://www.wago.com/793-5501/000-023">www.wago.com/793-5501/000-023</a> |
|--|--|

---

|   |  |
|---|--|
| <b>Item no.: 793-5501/000-024</b><br>WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; violet | <a href="http://www.wago.com/793-5501/000-024">www.wago.com/793-5501/000-024</a> |
|---|--|

---

|   |  |
|---|--|
| <b>Item no.: 793-501/000-002</b><br>WMB marking card; as card; not stretchable; plain; snap-on type; yellow | <a href="http://www.wago.com/793-501/000-002">www.wago.com/793-501/000-002</a> |
|---|--|

---

|   |  |
|---|--|
| <b>Item no.: 793-501/000-007</b><br>WMB marking card; as card; not stretchable; plain; snap-on type; gray | <a href="http://www.wago.com/793-501/000-007">www.wago.com/793-501/000-007</a> |
|---|--|

---

|  |  |
|--|--|
| <b>Item no.: 793-501/000-017</b><br>WMB marking card; as card; not stretchable; plain; snap-on type; light green | <a href="http://www.wago.com/793-501/000-017">www.wago.com/793-501/000-017</a> |
|--|--|

Subject to changes. Please also observe the further product documentation!





|   |  |
|---|--|
| <b>Item no.: 793-501/000-012</b><br>WMB marking card; as card; not stretchable; plain; snap-on type; orange   | <a href="http://www.wago.com/793-501/000-012">www.wago.com/793-501/000-012</a>   |
| <b>Item no.: 793-501/000-023</b><br>WMB marking card; as card; not stretchable; plain; snap-on type; green  | <a href="http://www.wago.com/793-501/000-023">www.wago.com/793-501/000-023</a>   |
| <b>Item no.: 793-501/000-006</b><br>WMB marking card; as card; not stretchable; plain; snap-on type; blue   | <a href="http://www.wago.com/793-501/000-006">www.wago.com/793-501/000-006</a>   |
| <b>Item no.: 793-501/000-005</b><br>WMB marking card; as card; not stretchable; plain; snap-on type; red  | <a href="http://www.wago.com/793-501/000-005">www.wago.com/793-501/000-005</a>   |
| <b>Item no.: 793-501</b><br>WMB marking card; as card; not stretchable; plain; snap-on type; white  | <a href="http://www.wago.com/793-501">www.wago.com/793-501</a>                   |
| <b>Item no.: 793-501/000-024</b><br>WMB marking card; as card; not stretchable; plain; snap-on type; violet   | <a href="http://www.wago.com/793-501/000-024">www.wago.com/793-501/000-024</a>   |
| <b>Item no.: 793-5501/000-005</b><br>WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; red    | <a href="http://www.wago.com/793-5501/000-005">www.wago.com/793-5501/000-005</a> |
| <b>Item no.: 793-5501/000-002</b><br>WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; yellow | <a href="http://www.wago.com/793-5501/000-002">www.wago.com/793-5501/000-002</a> |
| <b>Item no.: 793-5501/000-006</b><br>WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; blue   | <a href="http://www.wago.com/793-5501/000-006">www.wago.com/793-5501/000-006</a> |
| <b>Item no.: 793-5501</b><br>WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; white          | <a href="http://www.wago.com/793-5501">www.wago.com/793-5501</a>                 |
| <b>Item no.: 2009-115/000-012</b><br>WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; orange              | <a href="http://www.wago.com/2009-115/000-012">www.wago.com/2009-115/000-012</a> |
| <b>Item no.: 2009-115/000-006</b><br>WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; blue                | <a href="http://www.wago.com/2009-115/000-006">www.wago.com/2009-115/000-006</a> |
| Group marker carrier  |  |
| <b>Item no.: 870-183</b><br>Adaptor; gray   | <a href="http://www.wago.com/870-183">www.wago.com/870-183</a>                   |
| <b>Item no.: 870-182</b><br>Adaptor; gray   | <a href="http://www.wago.com/870-182">www.wago.com/870-182</a>                   |

Subject to changes. Please also observe the further product documentation!



Item no.: 870-184

Adaptor; gray

[www.wago.com/870-184](http://www.wago.com/870-184)


---

**Ferrule**


---



---

 Ferrule
 

---

Item no.: 216-123

Ferrule; Sleeve for 1 mm<sup>2</sup> / AWG 18; uninsulated; electro-tin plated; silver-colored[www.wago.com/216-123](http://www.wago.com/216-123)

Item no.: 216-122

Ferrule; Sleeve for 0.75 mm<sup>2</sup> / AWG 20; uninsulated; electro-tin plated; silver-colored[www.wago.com/216-122](http://www.wago.com/216-122)

Item no.: 216-124

Ferrule; Sleeve for 1.5 mm<sup>2</sup> / AWG 16; uninsulated; electro-tin plated[www.wago.com/216-124](http://www.wago.com/216-124)

Item no.: 216-132

Ferrule; Sleeve for 0.34 mm<sup>2</sup> / AWG 24; uninsulated; electro-tin plated[www.wago.com/216-132](http://www.wago.com/216-132)

Item no.: 216-121

Ferrule; Sleeve for 0.5 mm<sup>2</sup> / AWG 22; uninsulated; electro-tin plated; silver-colored[www.wago.com/216-121](http://www.wago.com/216-121)

Item no.: 216-131

Ferrule; Sleeve for 0.25 mm<sup>2</sup> / AWG 24; uninsulated; electro-tin plated; silver-colored[www.wago.com/216-131](http://www.wago.com/216-131)

Item no.: 216-223

Ferrule; Sleeve for 1 mm<sup>2</sup> / AWG 18; insulated; electro-tin plated; red[www.wago.com/216-223](http://www.wago.com/216-223)

Item no.: 216-222

Ferrule; Sleeve for 0.75 mm<sup>2</sup> / 18 AWG; insulated; electro-tin plated; gray[www.wago.com/216-222](http://www.wago.com/216-222)

Item no.: 216-221

Ferrule; Sleeve for 0.5 mm<sup>2</sup> / 20 AWG; insulated; electro-tin plated; white[www.wago.com/216-221](http://www.wago.com/216-221)

Item no.: 216-224

Ferrule; Sleeve for 1.5 mm<sup>2</sup> / AWG 16; insulated; electro-tin plated; black[www.wago.com/216-224](http://www.wago.com/216-224)

Item no.: 216-321

Ferrule; Sleeve for 0.25 mm<sup>2</sup> / AWG 24; insulated; electro-tin plated; yellow[www.wago.com/216-321](http://www.wago.com/216-321)

Item no.: 216-322

Ferrule; Sleeve for 0.34 mm<sup>2</sup> / 22 AWG; insulated; electro-tin plated; light turquoise[www.wago.com/216-322](http://www.wago.com/216-322)


---

**Tool**


---



---

 Operating tool
 

---

Item no.: 210-657

Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft; short; multicoloured

[www.wago.com/210-657](http://www.wago.com/210-657)

Item no.: 210-658

Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft; angled; short; multicoloured

[www.wago.com/210-658](http://www.wago.com/210-658)

Item no.: 210-720

Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft; multicoloured

[www.wago.com/210-720](http://www.wago.com/210-720)


---

 Subject to changes. Please also observe the further product documentation!
 

---

WAGO GmbH &amp; Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.



## Downloads

### Documentation

#### Bid Text

|                        |              |               |          |
|------------------------|--------------|---------------|----------|
| 869-316<br>X81 - Datei | 2019 年2月19 日 | xml<br>3.3 kB | Download |
|------------------------|--------------|---------------|----------|

|                        |              |                |          |
|------------------------|--------------|----------------|----------|
| 869-316<br>doc - Datei | 2017 年6月13 日 | doc<br>25.1 kB | Download |
|------------------------|--------------|----------------|----------|

#### Additional Information

|  |  |               |          |
|--|--|---------------|----------|
|  |  | pdf<br>2.3 MB | Download |
|--|--|---------------|----------|

## CAD/CAE-Data

### CAE data

|                           |  |     |          |
|---------------------------|--|-----|----------|
| EPLAN Data Portal 869-316 |  | URL | Download |
|---------------------------|--|-----|----------|

|                        |  |     |          |
|------------------------|--|-----|----------|
| WSCAD Universe 869-316 |  | URL | Download |
|------------------------|--|-----|----------|

|                      |  |     |          |
|----------------------|--|-----|----------|
| ZUKEN Portal 869-316 |  | URL | Download |
|----------------------|--|-----|----------|

### CAD data

|                      |  |     |          |
|----------------------|--|-----|----------|
| 2D/3D Models 869-316 |  | URL | Download |
|----------------------|--|-----|----------|

## Environmental Product Compliance

### Compliance Search

|  |  |     |          |
|--|--|-----|----------|
| Environmental Product Compliance 869-316 |  | URL | Download |
|--|--|-----|----------|

2-conductor terminal block; without push-buttons; with snap-in mounting foot; 1-pole; for plate thickness 0.6 - 1.2 mm; Fixing hole 3.5 mm Ø; 2.5 mm<sup>2</sup>; CAGE CLAMP®; 2,50 mm<sup>2</sup>; orange

## Installation Notes

### Commoning

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



Push jumper bars down firmly until fully inserted. When using multipole bars, push alternately on the right and then left side until installed.

Push-in type jumper bars 1 – 3 – 5 – 7 or  
1 – 4 – 7

upon request

#### Cover



Protective warning markers (280-405), with a black high-voltage symbol

#### Marking

---

Subject to changes. Please also observe the further product documentation!

Data sheet | Item number: 869-316

[www.wago.com/869-316](http://www.wago.com/869-316)



WMB markers in Mini-WSB marker slots

Translucent marking strip

Mini-WSB markers

Subject to changes. Please also observe the further product documentation!

---

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.