HDP24-24-31SE-L015 ✓ ACTIVE

DEUTSCH | DEUTSCH HD, DEUTSCH HDP

TE Internal #: HDP24-24-31SE-L015

Housing for Female Terminals, Wire-to-Wire, 31 Position, Sealable, Black, Wire & Cable, Power & Signal, Panel Mount, -67 – 257 °F [-55

– 125 °C]

View on TE.com >




Connectors > Automotive Connectors > Automotive Housings > DEUTSCH HDP20 Housings











Connector & Housing Type: Housing for Female Terminals

Mating Pin Diameter: 1.59 mm [.063 in]

Connector System: Wire-to-Wire

Number of Positions: 31

Sealable: Yes

All DEUTSCH HDP20 Housings (324)

Features

Product Type Features

Connector Shape	Circular
Connector & Housing Type	Housing for Female Terminals
Connector System	Wire-to-Wire
Sealable	Yes
Hybrid Connector	No
Primary Locking Feature	Contact Retainer
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Blank Cavity Position	0
Connector Modification	Threaded Adapter
Connector Seal Code	E Seal
	31



Electrical Characteristics	
Operating Voltage	250 VAC
Nominal Voltage Architecture	12 V, 24 V, 48 V
Body Features	
Cable Exit Angle	180°
Primary Product Color	Black
Contact Features	
Contact Size	Size 16
Contact Type	Socket
Mating Pin Diameter	1.59 mm[.063 in]
Contact Current Rating (Max)	13 A
Mechanical Attachment	
Terminal Position Assurance	No
Strain Relief	Add By Accessory
Mating Alignment Type	Guide Post
Mating Alignment	With
Connector Mounting Type	Panel Mount
Connector Mounting Type Housing Features	Panel Mount
	Panel Mount PA GF
Housing Features	
Housing Features Housing Material	
Housing Features Housing Material Dimensions	PA GF
Housing Features Housing Material Dimensions Connector Height	PA GF 47.63 mm[1.875 in]
Housing Features Housing Material Dimensions Connector Height Product Width	PA GF 47.63 mm[1.875 in] 50.8 mm[2 in]
Housing Features Housing Material Dimensions Connector Height Product Width Product Length	PA GF 47.63 mm[1.875 in] 50.8 mm[2 in] 58.67 mm[2.31 in]
Housing Features Housing Material Dimensions Connector Height Product Width Product Length Compatible Insulation Diameter Range	PA GF 47.63 mm[1.875 in] 50.8 mm[2 in] 58.67 mm[2.31 in]
Housing Features Housing Material Dimensions Connector Height Product Width Product Length Compatible Insulation Diameter Range Usage Conditions	PA GF 47.63 mm[1.875 in] 50.8 mm[2 in] 58.67 mm[2.31 in] 1.35 – 2.69 mm[.053 – .106 in]
Housing Features Housing Material Dimensions Connector Height Product Width Product Length Compatible Insulation Diameter Range Usage Conditions Operating Temperature (Max)	PA GF 47.63 mm[1.875 in] 50.8 mm[2 in] 58.67 mm[2.31 in] 1.35 – 2.69 mm[.053 – .106 in]
Housing Features Housing Material Dimensions Connector Height Product Width Product Length Compatible Insulation Diameter Range Usage Conditions Operating Temperature (Max) Operating Temperature Range	PA GF 47.63 mm[1.875 in] 50.8 mm[2 in] 58.67 mm[2.31 in] 1.35 – 2.69 mm[.053 – .106 in]

IP67

20mm Flame Test per Standard UL-94

Degree of Protection

UL Flammability Rating



Packaging Features

Packaging Method	Box
Other	
Serviceable	Yes
Connector Position Assurance Capable	No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





TE Part # CAT-H3910-B128 DEUTSCH HD10 Backshells



TE Part # CAT-H396-CH8172 DEUTSCH HDP20 Housings



TE Part # CAT-H396-RC8382 Receptacle Protective Caps — DEUTSCH HDP20



TE Part # CAT-D48-SP729 **DEUTSCH Sealing Plugs**



TE Part # HD30-24BT BOOT, 24SZ, ST, GRY



TE Part # CAT-H396-B128 DEUTSCH HDP20 Backshells



TE Part # 24-D-PUNCH D-HOLE PUNCH, SIZE 24



TE Part # HD30-24BT-BK BOOT, 24SZ, ST, BLK



TE Part # 16-04477 GASKET, 24SZ, BLK, HD30



TE Part # HD30-24BT-90-BK BOOT, 24SZ, RA, BLK



TE Part # 0411-336-1605 EXT TOOL, SIZE 16, 16-20 AWG, E, **DRK BLU**



Also in the Series | DEUTSCH HD



Automotive Connector Caps & Covers




Automotive Housings(741)




Connector Seals & Cavity Plugs(10)



Insertion & Extraction Tools(11)



Other Automotive Connector Accessories(11)



PCB Headers & Receptacles(1)

Also in the Series | DEUTSCH HDP

Housing for Female Terminals, Wire-to-Wire, 31 Position, Sealable, Black, Wire & Cable, Power & Signal, Panel Mount, -67 – 257 °F [-55 – 125 °C]






Automotive Connector Caps & Covers (12)




Automotive Housings(331)



Connector Seals & Cavity Plugs(1)



Insertion & Extraction Tools(11)



Customers Also Bought



TE Part #HDP24-24-31SE-L017
DEUTSCH HDP20 Housings



TE Part #DRC16-70SB-P013
PLG, 70P, BLK, N, SEAL BOND, B



TE Part #DT04-2P-L012 REC, 2P, GRY, N, FLANGE









Documents

Product Drawings REC, 31P, BLK, E, THD, 16, S

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_HDP24-24-31SE-L015_C.2d_dxf.zip

Housing for Female Terminals, Wire-to-Wire, 31 Position, Sealable, Black, Wire & Cable, Power & Signal, Panel Mount, -67 – 257 °F [-55 – 125 °C]



English

Customer View Model

ENG_CVM_CVM_HDP24-24-31SE-L015_C.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_HDP24-24-31SE-L015_C.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English

Agency Approvals

UL Report

English